

10
09
10
09
10
09
10
n9



automotive
systems

09|10

S.C. AVALON TOOLS IMPEX SRL
Bucuresti ROMANIA
Tel/Fax: 021-630.12.42
Mobil: 0723-99 11 76 / 0764-22 03 71
E-mail: avalontools@yahoo.com / office@premiertc.ro
www.premiertc.ro

FESTOOL

Scule pentru cele mai exigente pretentii



Edited with the demo version of
Infix Pro PDF Editor

To remove this notice, visit:
www.iceni.com/unlock.htm



Orientare aplicatii

Doar cei ce intelegh munca clientilor pot sa faca masina perfecta. Tocmai din acest motiv masinile si accesoriile FESTOOL sunt testate ca si in practica. Rezultatul: cea mai buna calitate chiar si pentru cele mai mici parti si accesorii, o ergonomie, manevrabilitate si design perfect.

Inovatie

O scula atunci este buna cand se potriveste perfect in mana utilizatorului. Din acest motiv FESTOOL investeste mult nu doar in ergonomicie ci si in dezvoltarea si perfectionarea continua a masinilor pt adaptarea lor la nevoile clientilor si se incercă tot timpul sa se gaseasca solutii cat mai bune pentru imbunatatirea calitatii lucrarilor si usurarea muncii. Se pune foarte mare pret de asemenea pe eficientizarea muncii si sanatate.

Sistemul FESTOOL

Sculele sunt foarte bune si daca au accesoriile potrivite. De aceia la FESTOOL totul se potriveste perfect. De la vasta gama a accesoriilor pana la scula in sine, si toate impreuna cu o exhaustare perfecta pentru a se putea lucra intr-un mediu cat mai sanatos si curat. Asta numim noi sistem.

Scule pentru cele mai exigente pretentii

S.C. AVALON TOOLS IMPEX SRL

Bucuresti


avalontools@yahoo.com

www.premiertc.ro

GSM : 0723.99 11 76

Slefuire 01

Sistemul FESTOOL 08
Slefuitoare cu aer comprimat: masinile si utilizarea lor 11
Slefuitoare cu aer comprimat: accesorii 14
Slefuitoare electrice: masinile si utilizarea lor 18
Slefuitoare electrice: accesorii 26
Abrazive 30




Polisare 02

Sistemul FESTOOL 36
Masinile si utilizarea lor 38
Accesorii 42




Exhaustarea 03

Sistemul FESTOOL 48
Aspiratoare industriale mobile: unitatile si folosirea lor 50
Aspiratoare industriale mobile: accesorii 57
Aspiratoare centralizate stationare: unitatile si folosirea lor 67
Aspiratoare centralizate stationare: accesorii 68
Centre de lucru si accesorii 69




Aranjarea locului de munca 04

Sistemul FESTOOL 72
Folosirea sculelor 76
Accesorii 80




Gaurire si insurubare 05

Sistemul FESTOOL 84
Folosirea sculelor 86
Accesorii 88



Systainere si Sortainere 06

SYSTAINERE 95
SORTAINERE 98
Systainer-Port 98





Rapid. Usor. Bine.

FESTOOL isi optimizeaza in mod continu produsele si aduce noi solutii pe piata. Tocmai de aceea poti face munca rapid, usor si bine.

Functionalitatea si inovatiile impresionante a produselor noastre si a designului incontestabil nu lasa altceva decat dorinte. O lista completa a produselor noastre poate fi gasita la www.festool.co.uk

1994	SYSTAINER- pentru a munci fara sa cauti
1996	CDD 12 masina de gaurit si insurubat- prima masina cu acumulator FESTOOL
1998	RS 400 slefuitor orbital- special conceput pentru folosire usoara
2000	ES 150 slefuitor excentric- slefuire fara efort
2002	CT MINI aspirator mobil- curat, compact, dimensiunile mentinute la minim
2003	LEX2 150 slefuitor excentric cu aer comprimat- o gama de masini pentru toate tipurile de slefuire
2004	TDK 12, TDK 15,6 masini de gaurit si insurubat cu acumulator- putere la dimensiuni mici.
2004	ROTEX RO 125 slefuitor rotoexcentric- manevrabil, original si versatil.
2004	LRS 400 slefuitor orbital cu aer comprimat- special conceput pentru suprafete mari.
2005	Agenti de polisare in sticele- functional si usor de manevrat
2005	C 12 masina de gaurit si insurubat- decide diferentele
2006	ROTEX RO 150 slefuitor rotoexcentric- original, redesenat si mai sofisticat.



C 12 masina de gaurit si insurubat cu acumulator decide diferența
F*GOLD* a fost concepută în 2005

Din 2200 de participanți din 35 de țari, FESTOOL a fost unul din castigatorii premiului IF product design award.

Cei ce gandesc inainte si se implica **pot atinge performante mari.**

Stimate client,

There are probably only a few industries that are as technologically conscious, that desire innovations and that are so demanding as the automotive industry. Automotive painting plays a particularly important role.

Because, in addition to the technology and the high quality materials that are to be found in the interiors of vehicles, it is the time-consuming applied paints in many nuanced colours that contribute to a desired individualisation of vehicles and models. Designers speak of colours that are applied like a metallic skin over the metal pieces and that make the shape appear even more alive through targeted light reflections.


As a manufacturer of high quality and durable tools, we have set ourselves the goal of helping auto paint shops and vehicle manufacturers on their way to achieving perfect surface quality. And, with a specially developed range of electrical and compressed air tools, the right accessories, mobile and stationary extraction units, and consumables that are individually matched to particular applications, we are well prepared to meet this goal. Only those who think ahead can provide an impetus for achieving the highest performance. As a result, we are investing in the development of new products and application solutions. In system solutions that contribute to helping further optimise work processes, that contribute to meeting increasing quality standards, and last but not least - despite growing pressure on costs - that contribute to securing the profitability of your company today as well as in the future.

We hope that you enjoy our new 09/10 Festool automotive systems catalogue. Here's to successful co-operation as partners!

Michael Bayer, Authorised
Representative
Director of Marketing

Holger Schulz, Authorised
Representative
Director of Sales





Sanding tools

for ground breaking perfection.

It is only if the preparatory work is of optimal quality that faultless and outstanding surfaces can be achieved. Whether eccentric or rotating, at Festool, there is the right sander for every job so that you can effortlessly prepare any surface for painting. Because sanding is the foundation for achieving perfect results.

01

Slefuire | Sistemul de slefuire uscata

Masini de slefuit cu aer comprimat

Masini de slefuit electrice

5 trepte pentru suprafete perfecte

1 Preparare

Slefitor excentric cu aer comprimat
LEX 2 150/11



FESTOOL Titan 2
Granulatie P40-120
Cristal
Granulatie P40-100

2 Slefuire grosiera

Slefitor excentric cu aer comprimat
LEX 2 150/7



FESTOOL Titan 2
Granulatie P80-120
Cristal
Granulatie P40-120

3 Slefuire intermediara

Slefitor excentric cu aer comprimat
LEX 2 150/3



FESTOOL Titan 2
Granulatie P150-320

Slefitor orbital cu aer comprimat **LRS 93**



FESTOOL Titan 2
Granulatie P 80-120
Cristal
Granulatie P 40-120

Slefitor orbital cu aer comprimat **LRS 400**



FESTOOL Titan 2
Granulatie P 150-320

Slefitor rotoexcentric
ROTEX RO 150 FEQ



FESTOOL Titan 2
Granulatie P 40-120
Cristal
Granulatie P 40-100

Slefitor excentric
WTS 150/7



FESTOOL Titan 2
Granulatie P 80-120
Cristal
Granulatie P 40-120

Slefitor excentric
ETS 150/3



FESTOOL Titan 2
Granulatie P 150-320

Slefitor rotativ **RAS 115**



FESTOOL Saphir
Granulatie P 24-80

Slefitor orbital **RS 100 CQ**



FESTOOL Titan 2
Granulatie P 80-120

Slefitor orbital **RS 100 CQ**



sau
RS 200 EQ
RS 300 EQ

FESTOOL Titan 2
Granulatie P 150-320



Edited with the demo version of
Infix Pro PDF Editor

To remove this notice, visit:
www.iconi.com/unlock.htm

4 Slefuire fina

Slefuitor excentric cu aer comprimat
LEX 2 150/3



sau
LEX 2 125/3

FESTOOL **Titan 2**
Granulatie P 360-500

5 Slefuire ultra fina

Slefuitor excentric cu aer comprimat
LEX 2 150/3



sau
LEX 2 125/3

FESTOOL **Titan 2**
Granulatie P 800-3000
Platin 2
Granulatie S 1000 - 4000

Slefuirea umeda e de domeniul trecutului

Aceasta metoda de slefuire umeda e folosita in mod special in industria auto.
 Slefuirea uscata e mai eficienta cu 30% decat slefuirea umeda asta in privinta costurilor, dar mai sunt si alte avantaje.

Slefuire uscata

Slefuire umeda



Incarcarea hartiilor abrazive

Minora datorita principiului Jetstream

Partial depinde de suprafata

Durata de viata a hartiilor abrazive

Lunga, multumita sistemului de exhaustare

Lunga, datorita peliculei de apa

Timp necesar pentru slefuire

Approx. 50%

100%

Timp de asteptare

Nu

Lung deoarece suprafata slefuita trebuie sa se usuce

Risc de erori

Scazute

- Mari, deoarece fillerul si spatula sunt hidroscopic si e nevoie ca suprafata sa se usuce complet ca sa se vada defectele inainte de vopsire.
- Dupa vopsire, striatiile cauzate de slefuire pot fi vizibile deoarece presiunea exercitata in medie pe abrazive este mai mare cand se slefuieste cu mana si mai neregulata decat atunci cand se slefuieste cu masini de slefuit.

Metoda de lucru

Cu slefuitor excentric

Cu mana

Costuri

Mai mici cu **30%**

100%

Slefuitor excentric
ETS 150/3



sau
ETS 125

FESTOOL **Titan 2**
Granulatie P 360-500

Slefuitor excentric
ETS 150/3



sau
ETS 125

FESTOOL **Titan 2**
Granulatie P 800-3000
Platin 2
Granulatie S 1000 - 4000

Intreaga gama a abrazivelor FESTOOL
 poate fi gasita la pagina 30.



Edited with the demo version of
Infix Pro PDF Editor

To remove this notice, visit:
www.iceni.com/unlock.htm

Avantajele puterii in trei – Sistemul Festool IAS 2!

De ce sa te complici cand poate fi atat de simplu? Sistemul IAS 2 foloseste un singur furtun pentru trei operatiuni: aer comprimat, exhaustarea aerului uzat si exhaustarea prafului. Practic in loc de trei furtune avem unul singur, in plus masinile cu aer comprimat Festool se racordeaza usor la furtun si se pot schimba tot atat de usor.



No oil mist.

Because of the IAS 2 system exhaust air extraction method. Laborious cleaning is not necessary.

Better protection against dust.

Because of direct extraction into the IAS 2 system. Clean, virtually dust-free air and a clear view of the workpiece.

Antistatic feature.

Prevents electrostatic charge build-up during the extraction procedure.

The IAS 2 system.

A single hose for 3 functions: supplying compressed air, extracting exhaust air, extracting dust. Simple plug-in when changing tools, no tangled hoses, fewer tripping hazards.

Jetstream principle.

Results in significantly improved dust extraction with up to a 30% longer abrasive service life.

Effective protection against cold.

Because of the housing insulation manufactured from MPE foam, free of CFCs, you will never get cold fingers again!

Accessories.

You will find a suitable supply unit, a mobile extraction unit, IAS 2 connectors and hoses starting on page 14 as well as in the chapter entitled „Extraction“ that starts on page 50.

S.C. AVALON TOOLS IMPEX SRL

Bucuresti

www.premiertc.ro

E-Mail : avalontools@yahoo.com

GSM : 0723.99 11 76

● Compressed air

○ Exhaust air return hose

● Dust extraction



Edited with the demo version of
Infix Pro PDF Editor

To remove this notice, visit:
www.iceni.com/unlock.htm

Sanding | Compressed air tools



Compressed air orbital sanders **LRS 93 M** and **LRS 93 G**

- The tools are simple and easy to guide
- Preselection of speed and stroke
- Vibration Stop system for work that is less hazardous and less tiring
- Robust vane motor for a long service life
- StickFix sanding pads and abrasives for quick changes
- LRS 93 G with handle for secure control

Compressed air orbital sander **LRS 400**

- Lightweight and handy despite its size
- High material removal rate on large, flat surfaces
- Very good extraction
- Softgrip handle
- Vibration Stop system for work that is less hazardous and less tiring
- Robust vane motor for a long service life
- StickFix sanding pad and abrasives for quick changes



Technical data

Operating pressure (flow pressure)	6 bar
Speed	7,000 rpm
No. of strokes	14,000 min ⁻¹
Sanding stroke	4 mm
Air consumption at rated load	310 l/min
Sanding pad StickFix	93 x 175 mm
Weight	LRS 93 M LRS 93 G
	1.2 kg 1.4 kg



Technical data

Operating pressure (flow pressure)	6 bar
Speed	7,000 rpm
No. of strokes	14,000 min ⁻¹
Sanding stroke	4 mm
Air consumption at rated load	390 l/min
Sanding pad StickFix	80 x 400 mm
Weight	2.3 kg

Items included

	Order No.
LRS 93 M 1 sanding pad StickFix 93 x 175 mm (soft), 1 StickFix Titan 2 abrasive sheet, 1 bottle of LD-10 cleaning and lubricating oil (50 ml), in a box	692049
LRS 93 G 1 sanding pad StickFix 93 x 175 mm (soft), 1 StickFix Titan 2 abrasive sheet, 1 bottle of LD-10 cleaning and lubricating oil (50 ml), in a box	692050

Items included

	Order No.
LRS 400 1 sanding pad StickFix 80 x 400 mm (soft), 1 StickFix Titan 2 abrasive sheet, 1 bottle of LD-10 cleaning and lubricating oil (50 ml), in a box	692099

Accessories starting on page 14

Accessories starting on page 14



Sanding | Compressed air tools



Compressed air eccentric sander
LEX 2 125/3 and LEX 2 125/7

- Softgrip cap to prevent hand slip
- Dead man's switch for safety
- Clearly visible stroke indicator
- Jetstream sanding pad for optimal dust extraction
- Sanding pad brake provides a clean pattern
- Vibration Stop system for work that is less hazardous and less tiring
- Robust vane motor for a long service life
- StickFix, MPE sanding pad

Compressed air eccentric sander
LEX 2 150/3 and LEX 2 150/7

- Softgrip cap to prevent hand slip
- Dead man's switch for safety
- Clearly visible stroke indicator
- Jetstream sanding pad for optimal dust extraction
- Sanding pad brake provides a clean pattern
- Vibration Stop system for work that is less hazardous and less tiring
- Robust vane motor for a long service life
- StickFix, MPE sanding pad



Technical data

Operating pressure (flow pressure)	6 bar
Speed	8,000 rpm
No. of strokes	16,000 min ⁻¹
Sanding stroke	3 mm / 7 mm
Air consumption at rated load	390 l/min
Sanding pad diameter	125 mm
Weight	1.3 kg

Technical data

Operating pressure (flow pressure)	6 bar
Speed	8,000 rpm
No. of strokes	16,000 min ⁻¹
Sanding stroke	3 mm / 7 mm
Air consumption at rated load	390 l/min
Sanding pad diameter	150 mm
Weight	1.3 kg

Items included

LEX 2 125/3	691128
1 StickFix sanding pad Ø 125 (ultra-soft), 1 StickFix Titan 2 sanding disc, 1 bottle of LD-10 cleaning and lubricating oil (50 ml), operating tool, in a box	
LEX 2 125/7	691127
1 StickFix sanding pad Ø 125 (soft HT), 1 StickFix Titan 2 sanding disc, 1 bottle of LD-10 cleaning and lubricating oil (50 ml), operating tool, in a box	

Accessories starting on page 14

Items included

LEX 2 150/3	692095
1 StickFix sanding pad Ø 150 (ultra-soft), 1 StickFix Titan 2 sanding disc, 1 bottle of LD-10 cleaning and lubricating oil (50 ml), operating tool, in a box	
LEX 2 150/7	692094
1 StickFix sanding pad Ø 150 (soft), 1 StickFix Titan 2 sanding disc, 1 bottle of LD-10 cleaning and lubricating oil (50 ml), operating tool, in a box	

Accessories starting on page 14





**Compressed air eccentric sander
LEX 2 150/11**

- Softgrip cap to prevent hand slip
- Dead man's switch for safety
- Clearly visible stroke indicator
- Jetstream sanding pad for optimal dust extraction
- Sanding pad brake provides a clean pattern
- Vibration Stop system for work that is less hazardous and less tiring
- Robust vane motor for a long service life
- StickFix, MPE sanding pad

**Compressed air eccentric sander
LEX 2 185/7**

- Softgrip cap to prevent hand slip
- Dead man's switch for safety
- Clearly visible stroke indicator
- Jetstream sanding pad for optimal dust extraction
- Sanding pad brake provides a clean pattern
- Vibration Stop system for work that is less hazardous and less tiring
- Robust vane motor for a long service life
- StickFix, MPE sanding pad



Technical data

Operating pressure (flow pressure)	6 bar
Speed	7,000 rpm
No. of strokes	14,000 min ⁻¹
Sanding stroke	11 mm
Air consumption at rated load	390 l/min
Sanding pad diameter	150 mm
Weight	1.3 kg

Technical data

Operating pressure (flow pressure)	6 bar
Speed	8,000 rpm
No. of strokes	16,000 min ⁻¹
Sanding stroke	7 mm
Air consumption at rated load	390 l/min
Sanding pad diameter	185 mm
Weight	1.6 kg

Items included

LEX 2 150/11
1 StickFix sanding pad Ø 150 (soft HT), 1 StickFix Cristal sanding disc, 1 bottle of LD-10 cleaning and lubricating oil (50 ml), operating tool, in a box

Order No.

691130

Items included

LEX 2 185/7
1 StickFix sanding pad Ø 185 (soft), 1 StickFix Titan 2 sanding disc, 1 bottle of LD-10 cleaning and lubricating oil (50 ml), operating tool, in a box

Order No.

692096

Accessories starting on page 14

Accessories starting on page 14



Sanding | Accessories for compressed air tools

Compressed air tool connectors

Type

Order No.

Suction hoses



IAS 2 hose, antistatic¹⁾

Temperature resistant to +70°C in accordance with DIN IEC 312, leakage resistance ≤ 10 MΩ, in a box

Length 3.5 m	IAS 2-3500 AS	487901
Length 5 m	IAS 2-5000 AS	488176
Length 7 m Note: not for the combination of CT/SR plus ASA	IAS 2-7000 AS	488131
Length 10 m Note: not for the combination of CT/SR plus ASA	IAS 2-10000 AS	494006
Length 15 m Note: not for the combination of CT/SR plus ASA	IAS 2-15000 AS	494528



IAS 2 hose, non-antistatic

Temperature resistant up to +70°C, in a box

Length 3.5 m	IAS 2-3500	488132
Length 5 m	IAS 2-5000	488175
Length 7 m Note: not for the combination of CT/SR plus ASA	IAS 2-7000	488133

¹⁾ The antistatic function is only guaranteed when a dust extractor with antistatic equipment is used.

IAS 2 connectors



IAS 2 connector

for SRM 45, SRM 70 CT mobile dust extractors, for connection to IAS 2 hoses, integrated connector for compressed air supply via compressed air connection hose, antistatic model, for EAA in EW/DW version, in a box

IAS 2-A-ASA/CT/SRM45/70

454757



IAS2 dual connector

for simultaneous connection of 2 IAS 2 compressed air tools that are alternately operated (additional connector IAS 2-A-ASA/CT/SRM45/70 (454757) required), in a box

IAS 2-DA-CT

454758



Adapter

for connecting SR dust extractor, LE version, with IAS 2 hoses, antistatic model, integrated connector for compressed air supply, in a box

IAS 2-A-SR

488181

Supply units



for upgrading the energy box (starting with 2009 models) of the EW type (only electrical tool operation) to the EW/DW type for the combined operation of electric and compressed air tools, in a box Includes the following: compressed air module, maintenance unit, cable harness (electrical), pneumatic hoses

VE 2-EAA

495892



for converting the type EW boom arm (for models up to 2008, for electric tool operation only) to the type EW/DW for combined operation of electric and compressed air tools, in a box

VE 1-ASA

488508



for TC 3000, for compressed air supply to mobile dust extractors CTL, CTM 22/33 and Series SR 151, SR 200 dust extractors in LE versions, in a box

VE-TC 3000

454808



for the CT mobile dust extractor in the LE version, consisting of a quick drain outlet for the condensate, pressure regulator, oiler and oil-free compressed air with quick-couplings, in a box

VE-CT

452797



	Type	Order No.
Adapter		
	for connecting Festool IAS 2 tools to a compressed air line, for operation without a dust extractor, with silencer and coupling socket KS-1/4	AD 1/4-IAS 2 488311
	for using suction nozzles D 36 with IAS 2 hoses. Note: using IAS 2 hoses for direct dust extraction without this adapter will deposit dust at the connection points and damage the hose and compressed air tool	AD-IAS 2/D 36 488418
	for connecting an IAS compressed air tool to an IAS 2 hose	AD-IAS/IAS 2 487879
	rubber sleeve for connecting IAS 2 compressed air tools via an IAS 2 connector, for central extraction units, boom arms manufactured by Rupes, IVO and Herkules, as well as Rupes power boxes	IAS 2-ZA 489222
	IAS 2 connector with closing valve for connecting IAS 2 suction hoses to central extraction units Herkules system IAS 2-S-ZA/Herkules 490 605 Hamach/Rupes system	IAS 2-S-ZA/Herkules 490605 IAS 2-S-ZA/Hamach 490603
Connecting sleeves		
	special adapter for SRM 312 LE-AS/SRM 70 LE-EC dust extractors, aluminium, only to be used in combination with IAS 2 connector IAS 2-A-SR	IAS 2-AK-B1 489263
	for connecting IAS 2 compressed air tools to central dust extraction systems via IAS 2 connectors, aluminium, can be cut for adapting to a particular central dust extraction system, diameter 58 mm	IAS 2-AK 488416
	for connecting IAS 2 compressed air tools to Herkules energy boxes via IAS 2 connectors, outer Ø 48 mm	IAS 2-FA 488417
Systainer accessories / replacement parts		
	SYSTAINER accessories 1x rotor, 4x vanes, 5x silencers, 5x Woodruff keys, 5x two clamps, gaskets and O-rings in various sizes	SYS-SERVICE LEX 489200
	Silencer for exhaust air outlet	U-3/8F 2309
	Cleaning and lubricating oil Special oil for preparing compressed air	
	1 litre	LD 10/1000 481722
	50 ml	LD-10/50 481713
	O-ring for IAS compressed air connectors	6 mm x 1 mm 204118




Sanding | Accessories for compressed air tools

LRS 93	LRS 400	LRB	for compressed air orbital sanders	Type	Order No.	
StickFix sanding pads						
				sanding pad, thin plate design Dimensions: 93 x 230 mm	SSH-STF-L93x230/0	486371
				Sanding pad, flatiron design Dimensions: 93 x 266 mm	SSH-STF-V93x266/14	486418
				Dimensions: 93 x 175 mm	SSH-STF-93x175/8	483905
				Dimensions: 80 x 400 mm	SSH-STF-80x400/17	493140
				Dimensions: 115 x 225 mm	SSH-STF-115x225/10-LRB	486919



Edited with the demo version of
Infix Pro PDF Editor



for compressed air eccentric sanders

	Sanding pads		
	hard version high edge wear resistance, for flat surfaces and narrow edges, connection thread M8	ST-STF-LEX 125/90/8-M8 H ST-STF-D150/8-M8 H	492284 484850
	soft version (HT) Temperature resistant Velcro for general use on flat and curved surfaces, for robust use of grit sizes up to P 220, connection thread M8	ST-STF-LEX 125/90/8-M8 W-HT ST-STF-D150/8-M8 W-HT	492286 491935
	soft version (general purpose) for general use on flat and curved surfaces, connection thread M8	ST-STF-D150/8-M8 W ST-STF-D185/16-M8 W	486381 490514
	soft version (general purpose) for Hamach/Rupes/Orka/Dessouter BR3/E/ST/E ST, TA151ST, for Orka: ROA1 D/E, DAA1 D/E, for Desoutter: Mod. 575, Mod. 576 Connection thread 5/16"	ST-STF-D150/8-5/16" W	487971
	ultra-soft version elastic construction, for high arches and curves, connection thread M8	ST-STF-LEX 125/90/8-M8 SW ST-STF-D150/8-M8 SW ST-STF-D185/16-M8 SW	492288 486382 490526
	Interface pad as damping element between sanding disc and sanding pad for sanding contoured parts and fine sanding with an eccentric sander		
	height 15 mm, diameter 120 mm, bolt circle diameter 90 mm	IP-STF-D120/90/8	492271
	height 15 mm, diameter 145 mm	IP-STF-D145/8-STF	492212
	Guide coat black for visually checking the surface to be sanded		
	set, consisting of hand sanding block and 2 cartridges of guide coat black powder	HB/Refill 2x30g	495939
	refill cartridge, 2 each	refill 2 x 30 g	495940

Sanding | Electric tools



Gear-driven eccentric sander ROTEX RO 125

- Compact, lightweight and handy for less tiring work
- Three tools in one for coarse sanding, fine sanding and polishing, resulting in low investment costs and a considerable reduction in working times
- Dustproof gear unit for a long service life
- Jetstream sanding pad for optimal dust extraction
- Quick set-up times because FastFix sanding pads can be changed without the use of any tools



Technical data

Power consumption	500 W
Speed	ROTEX curved track motion Eccentric motion
Sanding stroke	3.6 mm
FastFix sanding pad Ø	125 mm
Dust extraction connection Ø	27 mm
Weight	1.9 kg

Gear-driven eccentric sander ROTEX RO 150

- Coarse sanding, fine sanding, polishing
- ROTEX rotary motion for efficient material removal
- Eccentric motion for high quality surfaces that are free of scratches
- Ideal ergonomic grip positions
- Jetstream sanding pad for optimal dust extraction
- Quick set-up times because FastFix sanding pads can be changed without the use of any tools



Technical data

Power consumption	720 W
Speed	ROTEX curved track motion Eccentric motion
Sanding stroke	5 mm
FastFix sanding pad Ø	150 mm
Dust extraction connection Ø	27 mm
Weight	2.3 kg

Items included

RO 125 FEQ-Plus	Order No.
StickFix sanding pad Ø 125 mm (soft HT), StickFix sanding disc, Festool PROTECTOR, in a SYS 2 SYSTAINER	571533


Accessories starting on page 26

Items included

RO 150 FEQ-Plus	Order No.
StickFix sanding pad Ø 150 mm (soft HT), 1 x Brilliant 2 abrasive sheet, Festool PROTECTOR, in a SYS 3 SYSTAINER	571570

RO 150 FEQ	Order No.
StickFix sanding pad Ø 150 mm (soft HT), 1 x Brilliant 2 abrasive sheet, Festool PROTECTOR, in a box	571612

Accessories starting on page 26



Coarse sanding




Fine sanding



Polishing

3in1



Coarse sanding



Fine sanding



Polishing

3in1

Edited with the demo version of
Infix Pro PDF Editor

To remove this notice, visit:
www.iceni.com/unlock.htm





Eccentric sander **WTS 150/7**

- Sanding pad brake for safe, flawless work with no reworking costs
- Extremely powerful for efficient work
- Jetstream sanding pad for optimal dust extraction

Eccentric sander **ETS 125**

- Sanding pad brake for safe, flawless work with no reworking costs
- 2 mm sanding stroke for outstanding surface quality
- Small, lightweight and extremely handy for less tiring work
- Jetstream sanding pad for optimal dust extraction



Technical data

Power consumption	400 W
Speed	2,600-6,000 rpm
Sanding stroke	7 mm
Interchangeable sanding pad Ø	150 mm
Dust extraction connection Ø	27 mm
Weight	1.9 kg

Technical data

Power consumption	200 W	
Speed	With electronic settings Without electronic settings	6,000-14,000 rpm 14,000 rpm
Sanding stroke	2 mm	
Interchangeable sanding pad Ø	125 mm	
Dust extraction connection Ø	27 mm	
Weight	1.1 kg	

Items included

WTS 150/7 E
StickFix sanding pad Ø 150 mm (soft HT), sanding disc, extra handle, operating tool, in a box

Order No.

571581

Items included

ETS 125 EQ
StickFix sanding pad Ø 125 mm (soft HT), 1 StickFix sanding disc, filter cassette, in a box

Order No.

571607

ETS 125 Q

StickFix sanding pad Ø 125 mm (soft HT), 1 StickFix sanding disc, filter cassette, in a box

Order No.

571603

Accessories starting on page 26

Accessories starting on page 26



Sanding | Electric tools



Eccentric sander **ETS 150/3**

- 3 mm sanding stroke for an outstanding surface finish
- Dual bearings for a long service life
- Weighs only 1.8 kg for particularly effortless work
- Sanding pad brake for safe, flawless work with no reworking costs
- Stepless speed preselection, constant speed even under load
- Jetstream sanding pad for optimal dust extraction



Technical data

Power consumption	310 W
Speed	6,000-10,000 rpm
Sanding stroke	3 mm
Interchangeable sanding pad Ø	150 mm
Dust extraction connection Ø	27 mm
Weight	1.8 kg

Eccentric sander **ETS 150/5**

- 5 mm sanding stroke for efficient material removal
- Dual bearings for a long service life
- Weighs only 1.8 kg for particularly effortless work
- Sanding pad brake for safe, flawless work with no reworking costs
- Stepless speed preselection, constant speed even under load
- Jetstream sanding pad for optimal dust extraction



Technical data

Power consumption	310 W
Speed	6,000-10,000 rpm
Sanding stroke	5 mm
Interchangeable sanding pad Ø	150 mm
Dust extraction connection Ø	27 mm
Weight	1.8 kg

Items included

ETS 150/3 EQ-C StickFix sanding pad Ø 150 mm (ultra-soft HT), 1 StickFix sanding disc, operating tool, in a box	571552
ETS 150/3 EQ StickFix sanding pad Ø 150 mm (soft HT), 1 StickFix sanding disc, filter cassette, operating tool, in a box	571543

Accessories starting on page 26

Items included

ETS 150/5 EQ-C StickFix sanding pad Ø 150 mm (ultra-soft HT), 1 StickFix sanding disc, operating tool, in a box	571553
ETS 150/5 EQ StickFix sanding pad Ø 150 mm (soft HT), 1 StickFix sanding disc, filter cassette, operating tool, in a box	571546

Accessories starting on page 26



So that nothing gets clogged – the Festool Jetstream principle!

Festool abrasives and tools work according to the patented Jetstream principle: an additional hole in the centre and two air ducts prevent a vacuum from forming in the centre during dust extraction.



Jetstream principle



Less dust build-up.

The result: Festool abrasives accumulate significantly less dust. The grit can work in an optimal manner and can provide better sanding results for a longer period of time.



Less heat.

Even after just 2 minutes of sanding with a regular sanding disc, the accumulated layers of dust generate heat. As a result of the Jetstream principle, the sanding area is kept substantially cooler.



Less clogging.

Heat causes dust particles to clump together. The abrasive clogs and becomes unusable (example: 2 minutes of sanding new paint). The Jetstream principle keeps the temperature low during sanding and effectively prevents clogging.



Jetstream

This means cash savings for you! With the Jetstream principle, you use abrasives more efficiently and extend their useful life by up to 30%.



StickFix sanding pads

with high temperature resistant Velcro® (HT pads)

Temperature resistant Velcro® and optimal adhesion of the abrasive medium.

Very good matching of the pad to the contour of the workpiece. The resulting better feel allows sanding of even small radius areas.

The Velcro has a long useful life, even under the toughest conditions.

The soft edge protects the workpiece when the sanding pad is applied.

More efficient material removal because of less slip between the pad and abrasive.

The Velcro® is prevented from wearing by the 5 mm lip without a Velcro layer.

Sanding | Electric tools



Orbital sander RS 100

- High economic efficiency thanks to an extremely high material removal rate and reduction gearing
- Vibration Stop provides smooth running and safer working conditions
- Turbo dust extraction provides a clear view of the working area and ensures a safe working environment



Technical data

Power consumption	620 W
Speed	6,000 rpm
Sanding stroke	5 mm
Interchangeable sanding pad Ø	115 x 225 mm
Dust extraction connection Ø	27 mm
Weight	3.3 kg

Orbital sander RS 100 C

- Centre of gravity optimally located for perfect results and less tiring work
- High economic efficiency thanks to an extremely high material removal rate and reduction gearing
- Vibration Stop provides smooth running and safer working conditions
- External dust extraction provides a particularly clean and safe workplace



Technical data

Power consumption	620 W
Speed	6,300 rpm
Sanding stroke	5 mm
Interchangeable sanding pad Ø	115 x 225 mm
Dust extraction connection Ø	27 mm
Weight	3.0 kg

Items included

RS 100 Q
1 StickFix sanding sheet, StickFix sanding pad 115 x 225 mm, filter cassette, in a box

Order No.

567757

Items included

RS 100 CQ
1 StickFix sanding sheet, StickFix sanding pad 115 x 221 mm, in a box

Order No.

567759

Accessories starting on page 27

Accessories starting on page 27





Orbital sander RS 200

- No reworking because an excellent sanding result is produced with the high rpm and the direct drive
- Large sanding base for efficient sanding over large areas
- Ability to sand up to the edges on three sides
- The enclosed dustproof bearing and extremely tear resistant MPE sanding pad ensure a long service life and high economic efficiency



Technical data

Power consumption	330 W	
Speed	With electronic settings Without electronic settings	4,000-10,000 rpm 10,000 rpm
Sanding stroke	2.4 mm	
Replaceable sanding pad	115 x 225 mm	
Dust extraction connection Ø	27 mm	
Weight	2.5 kg	

Orbital sander RS 300

- Different interchangeable sanding pads for an extremely wide range of applications
- Ergonomic shape ensures less tiring work, even on vertical surfaces and overhead
- Rugged bearings, sturdily mounted oscillators and an extremely tear resistant MPE sanding pad ensure a long service life and high economic efficiency



Technical data

Power consumption	280 W	
Speed	With electronic settings Without electronic settings	4,000-10,000 rpm 10,000 rpm
Sanding stroke	2.4 mm	
Replaceable sanding pad	93 x 175 mm	
Dust extraction connection Ø	27 mm	
Weight	2.3 kg	

Items included	Order No.
RS 200 EQ 1 StickFix sanding sheet, StickFix sanding pad 115 x 225 mm, filter cassette, in a box	567763
RS 200 Q 1 StickFix sanding sheet, StickFix sanding pad 115 x 225 mm, filter cassette, in a box	567764

Accessories starting on page 27

Items included	Order No.
RS 300 EQ 1 StickFix sanding sheet, StickFix sanding pad 93 x 175 mm, filter cassette, in a box	567489
RS 300 Q 1 StickFix sanding sheet, StickFix sanding pad 93 x 175 mm, filter cassette, in a box	567490

Accessories starting on page 27

Sanding | Electric tools



Orbital sander RTS 400

- A uniform sanding pattern and the ability to sand close to edges on three sides keeps reworking to a minimum
- The enclosed dustproof bearing and extremely tear resistant MPE sanding pad ensure a long service life and high economic efficiency
- Effective integral Turbo dust extraction
- Small, lightweight and extremely handy for less tiring work



Technical data

Power consumption	200 W	
Speed	With electronic settings Without electronic settings	6,000-14,000 rpm 14,000 rpm
Sanding stroke	2 mm	
Replaceable sanding pad	80 x 130 mm	
Dust extraction connection Ø	27 mm	
Weight	1.1 kg	

Items included

Order No.

RTS 400 EQ 1 StickFix sanding sheet, StickFix sanding pad 80 x 130 mm, filter cassette, in a box	567814
RTS 400 Q 1 StickFix sanding sheet, StickFix sanding pad 80 x 130 mm, filter cassette, in a box	567829

Accessories starting on page 27





Rotary sander RAS RAS 115

- The ergonomic design and the small 58 mm diameter of the housing ensure less tiring work
- High economic efficiency because the machine speed can be set specifically to remove paint coatings
- Optimum dust extraction ensures a clean workspace, a clear view of the work area and a safe working environment
- Speed preselection, controlled speeds
- Quick set-up times because FastFix sanding pads can be changed without the use of any tools



Technical data

Power consumption	500 W
Speed	1,350-3,800 rpm
Interchangeable sanding pad Ø	115 mm
Spindle thread	M14
Dust extraction connection Ø	27 mm
Weight	2.3 kg

Items included

RAS 115.04 E-Set
Stickfix sanding pad Ø 115 mm (soft), sanding pad 2F 115 mm diameter, StickFix sanding discs, extraction hood, protective cover, extra hand grip, operating tool, in a SYS 2 SYSTAINER

Order No.

570733

Accessories starting on page 28

Rotary sander RAS 180

- Particularly economical when used over large areas because the machine is designed for high material removal rates and fast work progress
- Thermal overload protection keeps tool costs low because it ensures a long service life
- Optimum dust extraction ensures a clean workspace, a clear view of the work area and a safe working environment
- Quick set-up times because FastFix sanding pads can be changed without the use of any tools



Technical data

Power consumption	1,500 W
Speed	550-2,650 rpm
Interchangeable sanding pad Ø	180 mm
Spindle thread	M14
Dust extraction connection Ø	27 mm
Weight	4.2 kg

Items included

RAS 180.03 E-AH
StickFix sanding pad Ø 180 mm (soft), 1 StickFix sanding disc, extraction hood with handle, operating tool, in a box

Order No.

570774



Accessories starting on page 28



Sanding | Electric tool accessories

**for gear-driven eccentric
Sanders and eccentric sanders**

Sanders and eccentric sanders		Type	Order No.
Sanding pads			
hard version			
	high edge strength, for flat surfaces and narrow edges		
	FastFix	ST-STF D125/8 FX-H	492127
	FastFix	ST-STF D150/8 FX-H	493915
	Connection thread M8	ST-STF D150/8 M8 H	484850
soft version			
temperature resistant Velcro®, for general use on flat and curved surfaces			
	FastFix	ST-STF D125/8 FX-W-HT	492125
	Connection thread M4	ST-STF ES125/90/8-M4 W-HT	492280
	FastFix	ST-STF D150/8 FX-W-HT	493916
	Connection thread M8	ST-STF D150/8 M8 W-HT	491935
ultra-soft version			
elastic construction, for high arches and curves			
	FastFix	ST-STF D125/8 FX-SW	492126
	Connection thread M4	ST-STF ES125/90/8-M4 SW	492282
	FastFix	ST-STF D150/8 FX-SW	493917
	Connection thread M8	ST-STF D150/8 M8 SW	486382
soft version			
for general use on flat and arched surfaces			
	Connection thread M8	ST-STF D150/8 M8 W	486381
	for Hamach/Rupes: BR3/E/ST/E ST, TA151ST, for Orka: ROA1 D/E, DAA1 D/E, for Desoutter: Mod. 575, Mod. 576; connection thread 5/16"	ST-STF D150/6-5/16" W	487971
Interface pad			
as damping element between sanding disc and sanding pad for sanding contoured parts and fine sanding with an eccentric sander			
	height 15 mm, diameter 120 mm, bolt circle diameter 90 mm	IP-STF-D120/90/8	492271
	height 15 mm, diameter 145 mm	IP-STF D145/8-STF	492212
Guide coat black			
for visually checking the surface to be sanded			
	set, consisting of hand sanding block and 2 cartridges of guide coat black powder	HB/Refill 2x30g	495939
	refill cartridge, 2 each	refill 2 x 30 g	495940

**for Orbital sanders****Type****Order No.****StickFix sanding pads**

Dimensions: 115 x 221 mm	SSH-STF-115x221/10 RS 1 C	488226
Dimensions: 115 x 225 mm	SSH-STF-115x225/10	483679
with edge protection Dimensions: 115 x 225 mm	SSH-STF-115x225/10-KS	485648
Dimensions: 93 x 175 mm	SSH-STF-93x175/8	483905
Sanding pad, flatiron design Dimensions: 93 x 266 mm	SSH-STF-V93x266/14	486418
Dimensions: 80 x 130 mm	SSH-STF-80x130/14	489252
Dimensions: 80 x 130 mm	SSH-STF-80x130/8	483906

Sanding pads for abrasive media that may be clamped

Dimensions: 115 x 221 mm	SSH 115X221/10-RS 1 C	492310
Dimensions: 115 x 225 mm	SSH-115X225/10	489629
with edge protection Dimensions: 115 x 225 mm	SSH-115x225/10-KS	485647
Dimensions: 93 x 175 mm	SSH-93x175/8	489630
Dimensions: 80 x 130 mm	SSH-80x130/8	491366

Lochfix

for making the Festool hole pattern		
Number of holes: 8; dimensions 93 x 175 mm	8L 93x175	481903
Number of holes: 10	10L 115x225	481523



Sanding | Electric tool accessories

RAS 115
RAS 180

for rotary sanders

Sanding pads (connection thread M14)



Sanding pads soft version
for general use on flat and arched surfaces

Type ST-STF-D115/0-M14 W **484173**
ST-STF-D180/0-M14 W **485253**



Sanding pad hard version
high edge strength, for flat surfaces and narrow edges

Type ST-STF-D115/0-M14 H **484172**



Sanding pad for fibre discs and Longlife fibre discs

Type ST-D115/0-M14/2F **485298**
ST-D180/0-M14/2F **485296**



Clamping nut
for mounting Fiberfix sanding discs

Type SM-M14/D115 **439581**



Flexible sanding pad

Type ST-D115/0-EL **439580**

Brushes (connection thread M14)



Applications

with plastic bristles, 2 each per package AHP-RAS D115/2 **484727**



Circular brush
plaited, for removing paint, rust, and for cleaning surfaces

Type RB-D115/M14 RAS115 **485096**



Cup brush
for removing rust and dross, for clean metallic surfaces, waved


Type TB-D80/M14 RAS115 **485097**



Cup brush
plaited, for removing paint, rust, and for cleaning surfaces

Type TB-D65/M14 RAS115 **485099**





Type	Order No.
Extra handle	ZG-RAS/RO 487865
Hand grip	BG-RO 150 495188
Spark trap for dust extractor for CT/CTL/CTM 11, 22, 33, 44, 55	D 50 FL 484733

SYSTAINER with inserts for abrasives



in SYSTAINER SYS 1	SYS-STF D 115	487432
in SYSTAINER SYS 1	SYS-STF D 125	489463
in SYSTAINER SYS 3	SYS-STF D 150	487431
in SYSTAINER SYS 3	SYS-STF 80x133	487435
in SYSTAINER SYS 2	SYS-STF 115x228	487433

The plug it system



plug it cables, rubber insulated cables		
Length 4 m	H05 RN-F/4	489421
Length 7.5 m	05 RN-F/7,5	489661



plug it cables, PUR coated		
Length 4 m	H05 BQ-F/4	489662
Length 7.5 m	H05 BQ-F/7,5	489663



plug it connector		
Replacement connector	RK-PLUG IT	489685



plug it kit for Festool power tools		
360 mm for RS 1, RS 1 C, DX 93, RO 150/RO 2, RAS 115, BF 1, PS 200/PS 2, KF 4	UBS-PUR 360 plug it	491144
420 mm for RS 2, RS 3, RS 400/RS 4, DS 400, ES 125, OF 1000, OF 900, ATF 55, AT 65, AP 55, AP 65, EHL 65	UBS-PUR 420 plug it	491145



Suction hose plug-it D 27 with plug it connector Diameter: 27 mm Length 3.5 m	plug it D 27x3,5m-AS	456746
---	----------------------	---------------



Sanding | Abrasives

Convincing in practice, not just in theory.

You can be sure that Festool has the right abrasive available for every type of tool and every type of application.

Whether coarse or fine sanding – the more compatible the abrasive is with the tool, the more efficient your work will be. And what will be the outcome? Better results! Because with Festool abrasives, you can exploit the technical potential of Festool sanders to the fullest while saving consumables, work, time and money.


	Applications	Materials
FESTOOL Cristal	High performance abrasives for paints, lacquers and fillers Coarse, rapid preliminary sanding	<ul style="list-style-type: none">• Paint and lacquer• Filler (polyester filler, 2-component materials)
Titan 2	High performance abrasives for repair compounds, fillers and paint work Preliminary, intermediate and final sanding	<ul style="list-style-type: none">• Primers• Fillers• 2-component materials• Water-dilutable paints• Topcoat light sanding / matt sanding prior to repainting• Ceramic paints• UV cured paint systems• VOC topcoats
Saphir	High performance abrasives for very heavy duty sanding Sanding thick coatings on hard subsurfaces	<ul style="list-style-type: none">• Sanding reinforced and fibre reinforced plastics (GRP, CFRP etc.)• Sanding well-set fillers• Fine sanding of uncoated, roughened metal surfaces• Deburring, rust removal, descaling
Platin 2	High performance abrasives for finishing work on high gloss paints and plastics Finishing	<ul style="list-style-type: none">• Finish sanding as preparation for polishing• acrylic glass, Plexiglas®• PUR high gloss paint• Ceramic paints• Water-dilutable paints• UV cured paint systems• VOC topcoats
Vlies	High performance abrasives for the light sanding, roughening, cleaning, degreasing and matting of paints, lacquers and metals	<ul style="list-style-type: none">• Removing oxidation (efflorescence) from light metals• Sanding non-ferrous and heavy metals down to bare metal• Sanding soldered joints and junctions at welded points down to bare metal• Lightly sanding old coats of paint before repainting



Edited with the demo version of
Infix Pro PDF Editor

To remove this notice, visit:


www.iceni.com/unlock.htm

RO 125
 ETS 125
 LEX 125
 RO 150, RO 150 E
 ETS 150
 WTS 150
 LEX 150


Ø 125 mm

**Cristal**

P 40	5	494027	P 40	50	494032
P 60	5	494028	P 60	50	494033
P 80	5	494029	P 80	50	494034
P 100	5	494030	P 100	100	494035
P 120	5	494031	P 120	100	494036
P 80	50	492966	P 360	100	492973
P 120	100	492967	P 400	100	492974
P 150	100	492968	P 500	100	494839
P 180	100	492969	P 800	100	495045
P 220	100	492970	P 1200	100	492363
P 240	100	492971	P 1500	100	492364
P 320	100	492972	3000	100	492365
P 24	25	493124	P 50	25	493126
P 36	25	493125	P 80	25	493127

Titan 2**Platin 2****Vlies**

Ø 150 mm

**Cristal**


P 40	5	494037	P 40	50	494042
P 60	5	494038	P 60	50	494043
P 80	5	494039	P 80	50	494044
P 100	5	494040	P 100	100	494045
P 120	5	494041	P 120	100	494046
P 40	50	493663	P 280	100	492342
P 60	50	493664	P 320	100	492343
P 80	50	492335	P 360	100	492344
P 100	100	492336	P 400	100	492345
P 120	100	492337	P 500	100	492346
P 150	100	492338	P 800	100	492347
P 180	100	492339	P 1200	100	492348
P 220	100	492340	P 1500	100	492349
P 240	100	492341			
P 24	5	484105	P 50	25	486390
P 24	25	486388	P 80	25	486391
P 36	25	486389	P 100	25	491357

Titan 2**Platin 2****Vlies**

S 400	15	492368	S 2000	15	492371
S 500	15	492369	S 4000	15	492372
S 1000	15	492370			
A 100	5	482778	S 800	5	482780
A 280	5	482779			



Sanding | Abrasives



Ø 185 mm



Cristal

Grit	Package contents	Order No.	Grit	Package contents	Order No.
P 40	50	495920	P 100	50	495923
P 60	50	495921	P 120	50	495924
P 80	50	495922			

Titan 2

P 80	50	492744	P 180	100	492748
P 100	100	492745	P 240	100	492749
P 120	100	492746	P 320	100	492750
P 150	100	492747	P 360	100	492751

Saphir

P 24	25	491484	P 36	25	491483
------	----	---------------	------	----	---------------

80 x 133 mm



Cristal

P 40	10	494052	P 40	50	494057		
P 60	10	494053	P 60	50	494058		
P 80	10	494054	P 80	50	494059		
P 100	10	494055	P 100	100	494060		
P 120	10	494056	P 120	100	494061		
Vlies		A 100	5	483580	S 800	5	483582
		A 280	5	483581			

80 x 400 mm



Cristal

P 40	50	494254	P 100	50	494257
P 60	50	494255	P 120	50	494258
P 80	50	494256			

Titan 2

P 40	50	493175	P 180	50	493179
P 60	50	493176	P 240	50	493616
P 80	50	493177	P 320	50	493617
P 120	50	493178			

93 x 178 mm



Titan 2

P 100	100	493554	P 320	100	493556
P 150	100	493555			

Vlies

A 100	5	483583	S 800	5	483585
A 280	5	483584			







Polishing systems for a brighter outlook.

Whether you polish out paint overruns, eliminate flaws in the paint, or polish to get a high gloss finish, you will find the perfect polishing system at Festool. You will make any paint shine brightly without a lot of reworking. Even if the prospects appear not very bright!

02

Polishing | The Festool system

3 steps to a perfect surface

1 Ultra-fine sanding 2 Preliminary polishing 3 Fine polishing



Special applications

Spot repair

Polishing out holograms



Unique removal of light reflections and holograms with the ROTEX curved track motion.

Polishing | Polishing tools



Rotary polisher **RAP 80**

- Ergonomic dome grip and optimal weight distribution for relaxed work
- Speed preselection, speed control, smooth start-up
- Polishing pad changing without tools thanks to spindle stop
- PoliStick system
- Temperature dependent overload protection



Technical data

Power consumption	500 W
Speed	750-2,300 rpm
Maximum polishing pad diameter	80 mm
Spindle thread	M14
Weight	1.6 kg

Items included

RAP 80.02 E
StickFix polishing pad Ø 80 mm,
1 extra handle, in a box

Order No.

570722

Accessories starting on page 42

Rotary polisher **RAP 150**

- Ergonomic dome grip and optimal weight distribution for relaxed work
- Speed preselection, speed control, smooth start-up
- PoliStick system
- Temperature dependent overload protection



Technical data

Power consumption	1,050 W
Speed	900-2,500 rpm
Maximum polishing pad diameter	150 mm
Spindle thread	M14
Weight	2.7 kg

Items included

RAP 150 FEQ
1 StickFix polishing pad Ø 150 mm,
1 extra handle, in a box

Order No.

570729

Accessories starting on page 42





Rotary polisher POLLUX 180

- Ergonomic dome grip and optimal weight distribution for relaxed work
- Accelerator switch, speed preselection, speed control, smooth start-up
- Polishing pad changing without tools thanks to spindle stop
- PoliStick system
- Temperature dependent overload protection
- Exceptional cooling in lower speed range - allows work under heavy loads

Gear-driven eccentric sander ROTEX RO 150

- Particularly economical to use
- 3-in-1 principle: coarse sanding, fine sanding and polishing
- For long term polishing out of holograms
- Quick set-up times because FastFix sanding pads can be changed without the use of any tools
- Ideal ergonomic grip positions



Technical data

Power consumption	1,500 W
Speed	800-2,400 rpm
Maximum polishing pad diameter	180 mm
Spindle thread	M14
Weight	3.6 kg

Technical data

Power consumption	720 W
Speed	ROTEX curved track motion 320-660 rpm Eccentric motion 3,300-6,800 rpm
Sanding stroke	5 mm
FastFix sanding pad Ø	150 mm
Dust extraction connection Ø	27 mm
Weight	2.3 kg

Items included

POLLUX 180 E
1 StickFix polishing pad Ø 180 mm,
1 extra handle, in a box

Order No.

570734

Items included

RO 150 FEQ-C
StickFix polishing pad Ø 150 mm,
handle, in a box

Order No.

571666

Accessories starting on page 42


Accessories starting on page 42



Coarse sanding



Fine sanding



Polishing

3in1

Edited with the demo version of
Infix Pro PDF Editor

To remove this notice, visit:
www.iceni.com/unlock.htm



Polishing | Polishing tools



Gear-driven eccentric sander ROTEX RO 125

- Particularly easy to use.
- For long term polishing out of holograms
- Quick set-up times because FastFix sanding pads can be changed without the use of any toolsLong service life because of the dustproof drive



Technical data

Power consumption	500 W	
Speed	ROTEX curved track motion Eccentric motion	300–600 rpm 3,000–6,000 rpm
Sanding stroke	3.6 mm	
FastFix sanding pad Ø	125 mm	
Dust extractor connection Ø	27 mm	
Weight	1.9 kg	

Items included

Order No.

RO 125 FEQ-Plus

571533

StickFix sanding pad Ø 125 mm (soft HT),
StickFix sanding disc, Festool PROTECTOR,
in a SYS 2 SYSTAINER

Accessories starting on page 42



3in1



Perfect solutions for gleaming surfaces – using the Festool polishing system.

Whether you are polishing out holograms or polishing VOC and UV paints, with the Festool polishing system, surfaces shine perfectly. Because the tools, polishing agents and accessories are perfectly matched to one another.

Polishing out holograms.



Holograms on painted surfaces are a thing of the past. The Festool polishing system guarantees high quality, hologram-free results every time - annoying reflections don't stand a chance!

The ROTEX curved track motion produces shiny, hologram-free surfaces; a combination of eccentric and rotary motion that maintains a low surface temperature. The ball grip makes the ROTEX easier to guide and lets you polish for longer periods of time.



For minor holograms on fresh, dark paint: particularly suited for this purpose is the fine black polishing sponge with a honeycomb surface in combination with MPA 11000 polish.



For stubborn holograms on well-set paints: for best results, use the fine white polishing sponge with the honeycomb surface in combination with MPA 11000 polish.



Surface protection. With MPA-V high gloss sealant, surfaces remain protected for long periods of time!



The perfect finish. After each polishing step, you can easily remove any residue by using the Festool microfibre cloth and the finish cleaner, and you can check the quality of the surface.



Polishing UV paints.



UV paints are being used more and more and Festool has responded to this growing trend. The Festool polishing system is perfect for quickly and flexibly removing flaws in UV paint and reduces subsequent finishing work.

Step 1: Sand away the surface flaw

Selectively polish out the flaw using the D 36 spot sander together with Titan 2 P2500/P3000 sanding stars.



Step 2: Re-sand the flaw

Finish up by polishing out the flaw using the ETS 125 EQ eccentric sander and Platin 2/S4000 D 125 abrasive.



Step 3: Cleaning

Cleaning the surface thoroughly is important if you want to achieve high quality results. Try and clean the surface between each working step!



Step 4: Polishing

Now you can polish the area that has a flaw using the RAP 150.03 E rotary polisher. The best way is with the premium sheepskin and the MPA 8000 fine polishing agent. While doing this, the polisher should not exceed 1,500 rpm so that the surface does not heat up unnecessarily. Of course, you can also use the ROTEX RO 150 FEQ here.



Step 5: Adjacent painted areas

We recommend using the fine white polishing sponge with honeycombed surface (Ø 150 mm) combined with MPA 10800 UV ceramic high gloss polish.

Polishing | Accessories

	Type	Order No.
Polishing agents		
	Sanding polish Package contents: 1 each, 500 ml bottle Package contents: 6 each, 500 ml bottles	MPA 6000/1 MPA 6000/6 492424 492419
	Fine sanding polish Package contents: 1 each, 500 ml bottle Package contents: 6 each, 500 ml bottles Canister size: 5 kg	MPA 8000/1 MPA 8000/6 MPA 8000/5 kg 493816 493817 494134
	High gloss polish Package contents: 1 each, 500 ml bottle Package contents: 6 each, 500 ml bottles	MPA 10000/1 MPA 10000/6 492426 492421
	Ceramic high gloss polish, very fine Package contents: 1 each, 500 ml bottle Package contents: 6 each, 500 ml bottles Canister size: 5 kg	MPA 11000/1 MPA 11000/6 MPA 11000/5 kg 492427 492422 493544
	UV ceramic high gloss polish Package contents: 1 each, 500 ml bottle	MPA 10800-UV/1 495562
	High gloss sealing Package contents: 1 each, 500 ml bottle	MPA-V/1 495223
	Finish cleaner for removing polish residue and grease spots Package contents: 1 each, 500 ml bottle	MPA-F 493066
	Microfibre cloth for a perfect paint finish Package contents: 2 each	MPA-Microfibre/2 493068

Sanding stars and spot sander

	Titan 2 sanding stars self-adhesive, in a pouch	
	Grit size P 2000, package contents: 100 each	SK D36/0 P2000 TI2/100 495059
	Grit size P 2000, package contents: 1,000 each	SK D36/0 P2000 TI2/1000 495058
	Grit size P 2500, package contents: 100 each	SK D36/0 P2500 TI2/100 495061
	Grit size P 2500, package contents: 1,000 each	SK D36/0 P2500 TI2/1000 495060
	Grit size P 3000, package contents: 100 each	SK D36/0 3000 TI2/100 495063
	Grit size P 3000, package contents: 1,000 each	SK D36/0 3000 TI2/1000 495062
	Grit size P 5000, package contents: 100 each	SK D36/0 5000 TI2/100 495065
	Grit size P 5000, package contents: 1,000 each	SK D36/0 5000 TI2/1000 495064
	Spot sander for D 36 sanding stars, package contents: 1 each	RH-SK D 36/1 493069



RAP 80, T 15+3	
RO 125	
RAP 150	
RO 150	
RO 150 FEQ	
POLLUX 180	
	●
	○
	○
	○
	○
	○
	●
	○
	○
	●
	○
	○
	●
	○
	○
	○
	○
	●
	○
	○
	○
	○
	●
	○
	○
	○
	○
	●
	○
	○
	○
	○
	●

01
02
03
04
05
06

Type Order No.

Polishing pad

for attaching polishing accessories

	with integrated silencer for optimal pressure distribution when polishing Ø: 70 mm, height: 20 mm, package contents: 1 each	PT-STF-D80-M14	488337
	Adapter for Festool stirring rods: for clamping in chucks, for sanding pads with M14 thread, for use in drills, for use in cordless drills with Ø 10 mm clamping range	AD-D10/M14	483944
	Ø: 125 mm, height: 25 mm, package contents: 1 each	PT-STF D125 FX-RO125	492128
	with integrated silencer for optimal pressure distribution when polishing; Ø: 125 mm, height: 25 mm, package contents: 1 each	PT-STF-D150-M14	488342
	Ø: 145 mm, height: 6 mm, package contents: 1 each	PT-STF-D150-M8	485748
	Ø: 130 mm, height: 10 mm, package contents: 1 each	PT-STF D150 FX-RO150	493914
	with integrated silencer for optimal pressure distribution when polishing; Ø: 165 mm, height: 30 mm, package contents: 1 each	PT-STF-D180-M14	488349



Polishing | Accessories

Type	Order No.
Polishing sponges	
	
yellow, coarse	
for polishing heavily weathered surfaces (preparation for painting)	
Ø: 80 mm, height: 20 mm, package contents: 5 each	PS-STF-D 80X20-G/5 493842
Ø: 125 mm, height: 20 mm, package contents: 1 each	PS-STF-D125X20-G/1 493843
Ø: 125 mm, height: 20 mm, package contents: 5 each	PS-STF-D125X20-G/5 493844
Ø: 150 mm, height: 30 mm, package contents: 1 each	PS-STF-D150X30-G/1 493845
Ø: 150 mm, height: 30 mm, package contents: 5 each	PS-STF-D150X30-G/5 493846
Ø: 180 mm, height: 30 mm, package contents: 1 each	PS-STF-D180X30-G/1 493847
Ø: 180 mm, height: 30 mm, package contents: 5 each	PS-STF-D180X30-G/5 493848
	
orange, medium	
for preliminary polishing when repairing paint flaws	
Ø: 80 mm, height: 20 mm, package contents: 5 each	PS-STF-D 80X20-M-OCS/5 493849
Ø: 125 mm, height: 20 mm, package contents: 1 each	PS-STF-D125X20-M-OCS/1 493850
Ø: 125 mm, height: 20 mm, package contents: 5 each	PS-STF-D125X20-M-OCS/5 493851
Ø: 150 mm, height: 30 mm, package contents: 1 each	PS-STF-D150X30-M-OCS/1 493852
Ø: 150 mm, height: 30 mm, package contents: 5 each	PS-STF-D150X30-M-OCS/5 493853
Ø: 180 mm, height: 30 mm, package contents: 1 each	PS-STF-D180X30-M-OCS/1 493854
Ø: 180 mm, height: 30 mm, package contents: 5 each	PS-STF-D180X30-M-OCS/5 493855
	
white, fine	
for preliminary polishing and finishing when working on dust inclusions and with high gloss polishing agents	
Ø: 80 mm, height: 20 mm, package contents: 5 each	PS-STF-D 80X20-F/5 493863
Ø: 125 mm, height: 20 mm, package contents: 1 each	PS-STF-D125X20-F/1 493864
Ø: 125 mm, height: 20 mm, package contents: 5 each	PS-STF-D125X20-F/5 493865
Ø: 150 mm, height: 30 mm, package contents: 1 each	PS-STF-D150X30-F/1 493866
Ø: 150 mm, height: 30 mm, package contents: 5 each	PS-STF-D150X30-F/5 493867
Ø: 180 mm, height: 30 mm, package contents: 1 each	PS-STF-D180X30-F/1 493868
Ø: 180 mm, height: 30 mm, package contents: 5 each	PS-STF-D180X30-F/5 493869
	
white, fine (honeycombed)	
for preliminary polishing and finishing when working on dust inclusions, for polishing out holograms	
Ø: 80 mm, height: 20 mm, package contents: 5 each	PS-STF-D 80X20-F-GEW/5 493870
Ø: 125 mm, height: 20 mm, package contents: 1 each	PS-STF-D125X20-F-GEW/1 493871
Ø: 125 mm, height: 20 mm, package contents: 5 each	PS-STF-D125X20-F-GEW/5 493872
Ø: 150 mm, height: 30 mm, package contents: 1 each	PS-STF-D150X30-F-GEW/1 493873
Ø: 150 mm, height: 30 mm, package contents: 5 each	PS-STF-D150X30-F-GEW/5 493874
Ø: 180 mm, height: 30 mm, package contents: 1 each	PS-STF-D180X30-F-GEW/1 493875
Ø: 180 mm, height: 30 mm, package contents: 5 each	PS-STF-D180X30-F-GEW/5 493876
	
beige, fine	
for removing paint flaws, for follow-up polishing when working on dust inclusions	
Ø: 80 mm, height: 20 mm, package contents: 5 each	PS-STF-D 80X20-F-OCS/5 493856
Ø: 125 mm, height: 20 mm, package contents: 1 each	PS-STF-D125X20-F-OCS/1 493857
Ø: 125 mm, height: 20 mm, package contents: 5 each	PS-STF-D125X20-F-OCS/5 493858
Ø: 150 mm, height: 30 mm, package contents: 1 each	PS-STF-D150X30-F-OCS/1 493859
Ø: 150 mm, height: 30 mm, package contents: 5 each	PS-STF-D150X30-F-OCS/5 493860
Ø: 180 mm, height: 30 mm, package contents: 1 each	PS-STF-D180X30-F-OCS/1 493861
Ø: 180 mm, height: 30 mm, package contents: 5 each	PS-STF-D180X30-F-OCS/5 493862

RAP 80, T 15+3
RO 125
RAP 150
RO 150
RO 150 FEQ
POLUX 180

01
02
03
04
05
06

Type Order No.

Polishing sponges



black, very fine

for work on sealants, for use with high gloss polishing agents

Ø: 80 mm, height: 20 mm, package contents: 5 each	PS-STF-D 80X20-SF-OCS/5	493877
Ø: 125 mm, height: 20 mm, package contents: 1 each	PS-STF-D125X20-SF-OCS/1	493878
Ø: 125 mm, height: 20 mm, package contents: 5 each	PS-STF-D125X20-SF-OCS/5	493879
Ø: 150 mm, height: 30 mm, package contents: 1 each	PS-STF-D150X30-SF-OCS/1	493880
Ø: 150 mm, height: 30 mm, package contents: 5 each	PS-STF-D150X30-SF-OCS/5	493881
Ø: 180 mm, height: 30 mm, package contents: 1 each	PS-STF-D180X30-SF-OCS/1	493882
Ø: 180 mm, height: 30 mm, package contents: 5 each	PS-STF-D180X30-SF-OCS/5	493883



black, very fine (honeycombed)

for polishing out holograms, for use with high gloss polishing agents

Ø: 80 mm, height: 20 mm, package contents: 5 each	PS-STF-D 80X20-SF-OCS/5	493884
Ø: 125 mm, height: 20 mm, package contents: 1 each	PS-STF-D125X20-SF-OCS/1	493885
Ø: 125 mm, height: 20 mm, package contents: 5 each	PS-STF-D125X20-SF-OCS/5	493886
Ø: 150 mm, height: 30 mm, package contents: 1 each	PS-STF-D150X30-SF-OCS/1	493887
Ø: 150 mm, height: 30 mm, package contents: 5 each	PS-STF-D150X30-SF-OCS/5	493888
Ø: 180 mm, height: 30 mm, package contents: 1 each	PS-STF-D180X30-SF-OCS/1	493889
Ø: 180 mm, height: 30 mm, package contents: 5 each	PS-STF-D180X30-SF-OCS/5	493890

Polishing felt



hard

for preliminary polishing of acrylic glass and paints

Ø: 80 mm, height: 10 mm, package contents: 5 each	PF-STF-D80x20-H/5	488339
Ø: 125 mm, height: 10 mm, package contents: 5 each	PF-STF-D125x20-H/5	493078
Ø: 150 mm, height: 10 mm, package contents: 1 each	PF-STF-D150x20-H	485970
Ø: 150 mm, height: 10 mm, package contents: 5 each	PF-STF-D150x20-H/5	488348
Ø: 180 mm, height: 15 mm, package contents: 5 each	PF-STF-D180x20-H/5	488355



soft

for follow-up polishing of acrylic glass and paints

Ø: 80 mm, height: 10 mm, package contents: 5 each	PF-STF-D80x20-W/5	488341
Ø: 125 mm, height: 10 mm, package contents: 5 each	PF-STF-D125x20-W/5	493077
Ø: 150 mm, height: 10 mm, package contents: 1 each	PF-STF-D150x20-W	485972
Ø: 150 mm, height: 10 mm, package contents: 5 each	PF-STF-D150x20-W/5	488347
Ø: 180 mm, height: 15 mm, package contents: 5 each	PF-STF-D180x20-W/5	488354

Sheepskins



Sheepskin

for polishing scratch resistant paints

Ø: 80 mm, height: 20 mm, package contents: 5 each	LF-STF-D80/5	490247
Ø: 125 mm, height: 20 mm, package contents: 5 each	LF-STF-D125/5	493079
Ø: 150 mm, height: 20 mm, package contents: 1 each	LF-STF-D150	484131
Ø: 180 mm, height: 20 mm, package contents: 1 each	LF-STF-D180	485248



Premium sheepskin

particularly suitable for UV paints, scratch resistant paints

Ø: 80 mm, height: 20 mm, package contents: 5 each	LF-PREM.-STF-D 80/5	493835
Ø: 125 mm, height: 20 mm, package contents: 1 each	LF-PREM.-STF-D125/1	493836
Ø: 150 mm, height: 20 mm, package contents: 1 each	LF-PREM.-STF-D150/1	493838
Ø: 180 mm, height: 20 mm, package contents: 1 each	LF-PREM.-STF-D180/1	493840



FESTOOL

CTM 33 LE SG



Mobile dust extractors for air that is really clean.

For a healthy working environment, it is important that paint and fine dust be extracted reliably from surfaces. For this reason, the Festool mobile dust extractors guarantee a high level of suction and an optimal filter bag volume. In short, our clever concept will convince you. You will have workpieces without dust residue and will always have clean air to breathe.

03

Extraction | The Festool system

Mobile extraction

electrical

with compressed air¹⁾

Mobile dust extractors



CTL MINI / MIDI
mobile dust extractors



CTL/CTM
mobile dust extractors



SR special extractor



Supply unit



IAS 2 connector

¹⁾ Extractor in LE version or retrofitted with DL module.

Stationary extraction



TURBO 3091 exhaust turbine



TURBO 4001 exhaust turbine



TURBO 7501 exhaust turbine



Boom arm (ASA)



Energy box (EAA)

See chapter entitled
„Workplace organisation“, page 72
The use of boom arms (ASA) and energy boxes
(EAA) is also possible in combination with Festool
CT/SR mobile dust extractors. Edited with the demo version of
Infix Pro PDF Editor

01
02
03
04
05
06

Suction hoses

Tools

Accessories



plug it suction hose



Suction hose AS



IAS 2 hose AS



Electric tool



Compressed air tool



plug it suction hose



Suction hose AS



IAS 2 connector



IAS 2 hose AS



Electric tool



Compressed air tool

- Electric tools (EW)
- Compressed air tools (DW)
- AS AS antistatic



Extraction | Mobile dust extractors



Mobile dust extractor **CTL MINI**

- The compact unit with a 10 litre container volume
- Approved for dust category L
- Antistatic function prevents static charge from developing during work
- Practical storage for hose and mains cable
- Infinitely variable suction power adjustment
- Locking brake to prevent from rolling away
- Attachment of SYSTAINERs via Sys-Dock
- Storage compartment for replacement filter bag
- Full utilisation of the filter bag in the container for maximum economic efficiency



Items included

CTL MINI

1 fitted filter bag, 1 replacement filter bag in storage compartment, 1 suction hose Ø 27 x 3,5 m-AS with extractor side angular rotating adapter, in a box

Order No.

583355

Technical data, see page 54.
Accessories starting on page 57

Mobile dust extractor **CTL MIDI**

- The compact unit with a 15 litre container volume
- Approved for dust category L
- Antistatic function prevents static charge from developing during work
- Practical storage for hose and mains cable
- Infinitely variable suction power adjustment
- Locking brake to prevent from rolling away
- Attachment of SYSTAINERs via Sys-Dock
- Storage compartment for replacement filter bag
- Full utilisation of the filter bag in the container for maximum economic efficiency



Items included

CTL MIDI

1 fitted filter bag, 1 replacement filter bag in storage compartment, 1 suction hose Ø 27 x 3,5 m-AS with extractor side angular rotating adapter, in a box

Order No.

583371

Technical data, see page 54.
Accessories starting on page 57



Mobile dust extractors **CTL 22-55**

- The mobile dust extractors with container volumes from 22 to 55 litres
- Approved for dust category L
- Antistatic function prevents static charge from developing during work
- Infinitely variable suction power adjustment
- Locking brake to prevent from rolling away
- Attachment of SYSTAINERs via Sys-Dock
- Hose storage available as standard for greater tidiness and safety (CTL 22 and CTL 33)
- Full utilisation of the filter bag in the container for maximum economic efficiency



Items included	Order No.
CTL 22 E SG 1 fitted filter bag, suction hose Ø 27 x 3,5 m-AS, hose storage, in a box	583385
CTL 33 E SG 1 fitted filter bag, suction hose Ø 27 x 3,5 m-AS, hose storage, in a box	583393
CTL 33 LE SG with LE compressed air connector with automatic supply air switch for Festool IAS 2 compressed air tools and those of other manufacturers, 1 fitted filter bag, suction hose Ø 27 x 3,5 m-AS, hose storage, in a box	583456
CTL 44 E 1 fitted filter bag, suction hose Ø 27 x 3,5 m-AS, push handle, in a box	583307
CTL 44 LE with LE compressed air connection with automatic supply air switch for Festool IAS 2 compressed air tools and those from other manufacturers, 1 fitted filter bag, suction hose Ø 27 x 3,5 m-AS, push handle, in a box	583330
CTL 55 E 1 fitted filter bag, suction hose Ø 27 x 3,5 m-AS, push handle, in a box	583310

Technical data, see page 54.
Accessories starting on page 57

Mobile dust extractors **CTM 22-55**

- The mobile dust extractors with container volumes from 22 to 55 litres
- Approved for dust category M
- Antistatic function prevents static charge from developing during work
- FlowDetect flow monitor for safety
- Locking brake to prevent from rolling away
- Attachment of SYSTAINERs via Sys-Dock
- Hose storage available as standard for greater tidiness and safety (CTM 22 and CTM 33)
- Full utilisation of the filter bag in the container for maximum economic efficiency



Items included	Order No.
CTM 22 E SG 1 fitted filter bag, suction hose Ø 27 x 3,5 m-AS, cover lid for extractor connection, hose storage, in a box	583458
CTM 33 E SG 1 fitted filter bag, suction hose Ø 27 x 3,5 m-AS, cover lid for extractor connection, hose storage, in a box	583460
CTM 33 LE SG with LE compressed air connection with automatic supply air switch for Festool IAS 2 compressed air tools and those from other manufacturers, 1 fitted filter bag, suction hose Ø 27 x 3,5 m-AS, cover lid for extractor connection, hose storage, in a box	583462
CTM 44 E 1 fitted filter bag, suction hose Ø 27 x 3,5 m-AS, cover lid for extractor connection, push handle, in a box	583308
CTM 44 LE with LE compressed air connection with automatic supply air switch for Festool IAS 2 compressed air tools and those from other manufacturers, 1 fitted filter bag, suction hose Ø 27 x 3,5 m-AS, cover lid for extractor connection, push handle, in a box	583313
CTM 55 E 1 fitted filter bag, suction hose Ø 27 x 3,5 m-AS, cover lid for extractor connection, push handle, in a box	583311

Technical data, see page 54.
Accessories starting on page 57



Extraction | Special application dust extractors



Special application dust extractor **SRM 45**

- Approved for dust category M
- FlowDetect flow monitor for safety
- Antistatic function prevents static charge from developing during work
- Continuously variable suction power adjustment for perfect suction power
- EC motor for continuous use and with a service life that is up to ten times longer than that of a universal motor
- Cable rewind to keep things tidy



Items included

SRM 45 LE-EC

Compressed air connector with automatic supply air switch, 1 filter bag, suction hose Ø 27 x 3,5 m-AS, in a box

Order No.

583288

Technical data, see page 54.
Accessories starting on page 57

Special application dust extractor **SRM 70/B1**

- Approved for dust category M
- Extraction of combustible, explosive dust from dust explosion categories St1, St2 and St3 in Zone 22 (previously Zone 11)
- Corresponds to ATEX directive 94/9/ECC (Type 22)/B1
- FlowDetect flow monitor for safety
- Antistatic function prevents static charge from developing during work
- Continuously variable suction power adjustment for perfect suction power
- EC motor for continuous use and with a service life that is up to ten times longer than that of a universal motor
- Cable rewind and push handle



Items included

SRM 70 LE-EC/B1

Compressed air connector with automatic supply air switch, 1 filter bag, suction hose Ø 27 x 3,5 m-AS, in a box

Order No.

583289

Technical data, see page 54.
Accessories starting on page 57



Special application dust extractor SRH 45

- Approved for dust categories M and H
- FlowDetect flow monitor for safety
- Antistatic function prevents static charge from developing during work
- Continuously variable suction power adjustment for perfect suction power
- Cable rewind to keep things tidy



Items included

Order No.

SRH 45 E1 filter bag, suction hose Ø 27 x 3,5 m-AS,
in a box**583287**

Technical data, see page 54.
Accessories starting on page 57

The aluminium sanding workplace from Festool

The safe solution for aluminium sanding.



Particularly when sanding aluminium, a perfectly equipped workplace is absolutely necessary. This is the only way that corrosion caused by contact can be avoided and explosions due to aluminium dust can be prevented.

The aluminium sanding workplace from Festool is therefore the perfect and safe solution. It conforms to the ATEX directive and, in addition, makes efficient and flexible work possible.

Perfectly protected:



Contact corrosion is caused by the following:

- alternately sanding both steel and aluminium vehicle parts with the same tools, the same sanding pads and the same abrasives
- incorporation of steel particles, which are created by the sanding process, into the surface of the aluminium


Extraction | Overview of mobile dust extractors



Technical data

Order No.	583355	583371	583385	583458	583393	583456	583460	583462
Dimensions (mm) L x W x H	440 x 340 x 420	440 x 340 x 470	625 x 380 x 550		625 x 380 x 660		625 x 380 x 660	
Weight (kg)	9.5	9.7		13.1		15.6		15.6
Container volume (litres)	10	15		22		33		33
Filter bag capacity (litres)	7.5	12.5		20		30		30
Design approval/dust category	L	L	L	M	L	L	M	M
Degree of filtration (%)	> 99		> 99	> 99.9		> 99		> 99.9
Flow volume (l/min)	max. 2,800				max. 3,800			
Filter surface area (cm ²)	5,000				14,000			
Vacuum (Pa)	max. 20,000 (200 mbar)				max. 23,000 (230 mbar)			
Power consumption (watts)	400-1,200				350-1,200			
Load connected to electrical outlet			max. 2,400 watts (depending upon country-specific regulations)					
Mains cable				Rubber insulated, 7.5 m long				
Items included				1 antistatic suction hose D 27 x 3,5 m-AS / 1 filter bag ¹⁾				

Combination with ASA/EAA




Combination with TC 2000 / TC 3000²⁾



Compressed air automatic On/Off switch

Automatic On/Off switch for electric tools



Design approvals, dust classes in accordance with EN 60335-2-69

Design approval	Degree of filtration, filter system	Suitability
Dust category L	> 99 %	Hazardous dust with TLVs > 1 mg/m ³ and for NON-hazardous dust
Dust category M	> 99.9 %	Hazardous dust with TLVs > 0.1 mg/m ³ and wood dust
Dust category H	> 99.995 %	Hazardous dust with TLVs < 0.1 mg/m ³ and carcinogenic dust
ATEX/B1, dust category M	> 99.9 %	Explosive dust from explosion classes ST1, ST2 and ST3 in Zone 22

TLV = Threshold Limit Value / Sources: EN 60335-2-69 and IEC 60335-2-69 Appendix AA

¹⁾ For CTL MINI and CTL MIDI: suction hose D 27 x 3,5 m-AS with angular rotating adapter, 1 fitted filter bag and a replacement filter bag packed in the storage compartment.

²⁾ CT 33 without hose storage.



CTL 44 E

CTL 44 LE

CTM 44 E

CTM 44 LE

CTL 55 E

CTM 55 E

SRM 70 LE-EC/B1


SRM 45 LE-EC

SRH 45 E

Special application dust extractors



583307	583330	583308	583313	583310	583311	583289	583288	583287
710 x 380 x 935				710 x 380 x 935		580 x 605 x 970		506 x 476 x 655
20				22		25		14
44				55		70		45
42				50		40		24
L	L	M	M	L	M	ATEX/B1 + M	M	H
> 99		> 99.9		> 99	> 99.9	> 99.9	> 99.9	> 99.995
		max. 3,800				3,600	3,600	3,100
		14,000				3,000	3,000	10,000
				max. 23,000 (230 mbar)				
				350-1,200				
				max. 2,400 watts (depending upon country-specific regulations)				
				Rubber insulated, 7.5 m long				
				1 antistatic suction hose D 27 x 3,5 m-AS / 1 filter bag				



Combination possible

Festool recommendation

Standard equipment

Compressed air module may be retrofitted

Extraction – safe, economic, healthier.

To protect your health, Festool develops mobile dust extractors that can extract even the smallest of particles. Reliably and safely. At the same time, the dust extractors are extremely economical to use because the filter bags do not have to be replaced very often. This is the way that a perfect system is supposed to function.



Safety.

Because they have features such as flow volume control¹⁾ and shutoff delay, as well as clever details such as a cable rewind, push handle, hose storage and much more, mobile dust extractors from Festool provide the greatest safety at your workplace.

Your health.

The perfect combination of Festool compressed air and electric tools guarantee you a workplace that is almost free from dust - even when sanding aluminium²⁾.



Economic efficiency.

You will be completely satisfied with Festool mobile dust extractors because of their long service life, high suction power, and their optimal use of the filter bag volume. You will work economically and efficiently.

Festool thinks in terms of systems.

With its two production series, three special application dust extractors, and a total of 17 models, as well as its comprehensive and perfectly matched line of accessories, Festool dust extraction systems offer you the right solution for all your requirements.



All the extractor system components can be found starting on page 57.

¹⁾ Only for dust category M extractors.

²⁾ When sanding aluminium, compressed air tools and the SRM 70 LE-EC/B1 special application dust extractor must be used.

Extraction | Accessories

01
02
03
04
05
06

for the CT mobile dust extractor and the SR dust extractor

Type

Order No.

Antistatic suction hose¹⁾

Temperature resistant to +70°C in accordance with DIN IEC 312,
leakage resistance ≤ 10 MΩ, in a box



Diameter: 22 mm

With angular rotating adapter and connector sleeve, length: 3.5 m D 22x3,5m-AS **456745**

Diameter: 27 mm

With rotating adapter and connection sleeve, length: 3.5 m D 27x3,5m-AS **452878**

With rotating adapter and connection sleeve, length: 5 m D 27x5m-AS **452880**

Available by the metre (w/o rotating adapter/connection sleeve) D 27 MW-AS **452384**

Special design only for SRM 312 LE-AS/ SRM 70 LE-EC, with angular rotating adapter and connection sleeve, length: 3.5 m D 27x3,5m-AS/B1 **489266**

Diameter: 36 mm

With rotating adapter and connection sleeve, length: 3.5 m D 36x3,5m-AS **452882**

With rotating adapter and connection sleeve, length: 5 m D 36x5m-AS **452884**

With rotating adapter and connection sleeve, length: 7 m D 36x7m-AS **452886**

Available by the metre (w/o rotating adapter/connection sleeve) D 36 MW-AS **452385**

Diameter: 50 mm

With rotating adapter and connection sleeve, length: 2.5 m D 50x2,5m-AS **452888**

With rotating adapter and connection sleeve, length: 4 m D 50x4m-AS **452890**

Available by the metre (w/o rotating adapter/connection sleeve) D 50 MW-AS **452386**

Diameter: 27 mm

With plug it connector, length: 3.5 m plug it D 2 x3,5m-AS **456746**



¹⁾ The antistatic function is only guaranteed when used with dust extractors that have antistatic equipment.

Non-antistatic suction hose

Temperature resistant up to +70°C, in a box



Diameter: 27 mm

With rotating adapter and connection sleeve, length: 3.5 m D 27x3,5m **452877**

With rotating adapter and connection sleeve, length: 5 m D 27x5m **452879**

Available by the metre (w/o rotating adapter/connection sleeve) D 27 MW **452383**

Diameter: 36 mm

With rotating adapter and connection sleeve, length: 3.5 m D 36x3,5 m **452881**

With rotating adapter and connection sleeve, length: 5 m D 36x5 m **452883**

With rotating adapter and connection sleeve, length: 7 m D 36x7 m **452885**

Available by the metre (w/o rotating adapter/connection sleeve) D 36 MW **454157**

Diameter: 50 mm

With rotating adapter and connection sleeve, length: 2.5 m D 50x2,5m **452887**

With rotating adapter and connection sleeve, length: 4 m D 50x4m **452889**


Available by the metre (w/o rotating adapter/connection sleeve) D 50 MW **454158**



Extraction | Compressed air extractor accessories

CT/CTL/CTM 11
CT/CTL/CTM 22
CT/CTL/CTM 33
CT/CTL/CTM 44
CT/CTL/CTM 55

for mobile dust extractor CT, compressed air

	Type	Order No.
	Compressed air module for upgrading CT version E mobile dust extractors into the LE version, with additional automatic On/Off compressed air switch, in a box	DLM-CT 452829
	Supply unit consisting of quick drain outlet for the condensate, pressure regulator, oiler and oil-free compressed air outlet with quick-couplings, in a box	VE-CT 452797
	IAS 2 connector for connection to IAS 2 hoses, integrated connector for compressed air supply via compressed air connection hose, antistatic model, for EAA in EW/DW version, in a box	IAS 2-A-ASA/CT/SRM45/70 454757
	IAS 2 dual connector for simultaneous connection of 2 IAS 2 compressed air tools that are operated alternately (additional connector IAS 2-A-ASA/CT/ SRM45/70 (454757) required), in a box	IAS 2-DA-CT 454758

Suction hoses



IAS 2 hose, antistatic¹⁾

Temperature resistant to +70°C in accordance with DIN IEC 312, leakage resistance ≤ 10 MΩ, in a box

Length 3.5 m	IAS 2-3500 AS	487901
Length 5 m	IAS 2-5000 AS	488176
Length 7 m. Note: not for the combination of CT/SR plus ASA	IAS 2-7000 AS	488131
Length 10 m. Note: not for the combination of CT/SR plus ASA	IAS 2-10000 AS	494006
Length 15 m. Note: not for the combination of CT/SR plus ASA	IAS 2-15000 AS	494528



IAS 2 hose, non-antistatic

Temperature resistant up to +70°C, in a box

Length 3.5 m	IAS 2-3500	488132
Length 5 m	IAS 2-5000	488175
Length 7 m. Note: not for the combination of CT/SR plus ASA	IAS 2-7000	488133

¹⁾The antistatic function is only guaranteed when used with dust extractors that have antistatic equipment.

Adapters



for connecting Festool IAS 2 tools to a compressed air line, for operation without dust extraction, with silencer and coupling socket KS-1/4

AD 1/4-IAS 2

488311



for using D 36 suction nozzles with IAS 2 hoses. Note: using IAS 2 hoses for direct dust extraction without this adapter will deposit dust at the connection points and will damage the hose and compressed air tool

AD-IAS 2/D36

488418



for connecting an IAS compressed air tool to an IAS 2 hose

AD-IAS/IAS 2

487879



rubber sleeve for connecting IAS 2 compressed air tools via an IAS 2 connection, for central extraction units, boom arms manufactured by Rupes, IVO and Herkules, as well as Rupes energy boxes


IAS 2-ZA

489222




SRM 45 LE-EC	SRM 70 LE-EC	SRH 45	SRM 312 LE-AS	SR 200	SR 300
●	●				
○	○	○	○	○	○
○	○	○	○	●	●
○	●	○	○	○	○
●	○	○	○	○	○
○	●	○	○	○	○
○	○	●	○	○	○
○	○	○	○	●	○
○	○	○	○	○	●
○	○	○	○	●	●

for dust extractor SR, compressed air

	IAS 2 connector for connection to IAS 2 hoses, integrated connector for compressed air supply via compressed air connection hose, antistatic model, for EAA in EW/DW version, in a box	IAS 2-A-ASA/CT/SRM45/70	454757
	Adapter for connecting SR dust extractor, LE version, with IAS 2 hoses, antistatic model, integrated connector for compressed air supply, in a box	IAS 2-A-SR	488181
	Connecting sleeve Adapter, aluminium, only to be used in connection IAS 2 connector IAS 2-A-SR	IAS 2-AK-B1	489263
Supply units			
	for LE version dust extractors (integrated automatic On/Off switch for compressed air tool)	VE-SRM 45	493823
		VE-SRM 70	493824
	for LE version dust extractors (integrated automatic On/Off switch for compressed air tool)	VE-SR 200	488525
		VE-SR 300	488090



Extraction | Accessories

**CT filters and filter bags****Main filter****Wet filter****Filter bag**

with spunbond outer layer, particularly resistant to tearing, for extracting extremely fine

Longlife filter bag

only to be used for extracting dust that is non-hazardous

**SR filters and filter bags****Absolute filter**

BIA approved

**Filter bag**

BIA approved



Extraction | Accessories

	Type	Order No.
SR filters and filter bags for discontinued models		
	for SR 5, SR 200, SR 201 Package contents: 1 each	AB-FI/U 485808
	for SR 151 Package contents: 1 each	AB-FI 488461
	for SR 6, SR 12, SR 14, SR 202, SR 203, SR 212, SR 301, SR 302, SR 303 Application category C/M Package contents: 1 each	AB-FI/C 486241
	for SRM 152, SRM 312 Application category C/M Package contents: 1 each	AB-FI/C 488924
	for SR 6, SR 12, SR 14, SR 15 Application category K1/H Package contents: 1 each	MI-FI/K1 486145
	for SRH 204 Application category K1/H Package contents: 1 each	MI-FI/H 489221
	for SR 12, SR 11, SR 10 Package contents: 1 each	AB-FI/U 485809
	Long service life prefilter as a replacement for the FIS filter bag for extracting coarse dirt, for use with all SR extractors, except for SR 15, SRH 204, SRM 312, SRM 45/70, SRH 45	VF-Multi 451230
	Two-ply filter bag BIA approved	
	for SR 5, SR 6 for materials with TLVs Package contents: 5 each	FIS-SR 5/6 /5 483143
	for SR 5, SR 6 Package contents: 20 each	FIS-SR 5/6 /20 487875
	for materials with TLVs Package contents: 5 each	FIS-SR 12/14 /5 483142
	for SR 151, SRM 152 Package contents: 5 each	FIS-SR 150 /5 488460
	for SR 200, SR 201, SR 203 Package contents: 5 each	FIS-SR 200 /5 487070
	for SR 200, SR 201, SR 203 Package contents: 20 each	FIS-SR 200 /20 487874
	for SR 301, SR 303, SRM 312 Package contents: 5 each	FIS-SR 300 /5 487790
	for SR 15, SR 12, SR 14 for substances with TLVs and carcinogenic substances as defined by GefStoffV35, BIA approved Package contents: 5 each	FIS-SR 15 /5 483889
	for SR 202, SR 212, SRH 204, SR 200, SR 201, SR 203 Package contents: 5 each	FIS-SR 202 /5 487482
	for SR 302, SR 301, SR 303, SRM 312 Package contents: 5 each	FIS-SR 302 /5 488439
	Air filter cassette for SRM 312 (1 each delivered), can be used with SR 151, SRM 152, SR 200, SR 201, SR 202, SR 203, SR 212, SRH 204, SR 301, SR 302, SR 303, protects motors when there is a great deal of dust in the air	LFC-SR 200 487540



**for CT mobile dust extractors
and SR dust extractors**
Type
Order No.
Hose sleeves

Rotating adapter for antistatic suction hoses

Hose sleeve for connection to the inlet nozzle of a dust extractor

 for suction hose D 27, outside Ø 58 mm **452892**

 for suction hose D 36, outside Ø 58 mm **452894**

 for suction hose D 50, outside Ø 58 mm **452896**

Angular rotating adapter for antistatic suction hose

for suction hoses D 22 and D 27 on the CTL MINI and the CTL MIDI


Rotating adapters

Hose sleeve for connection to the inlet nozzle of a dust extractor

 for suction hose D 27, outside Ø 58 mm **452891**

 for suction hose D 36, outside Ø 58 mm **452893**

 for suction hose D 50, outside Ø 58 mm **452895**

Antistatic connector sleeves

for suction side connections (electric tool or suction nozzle)

 for suction hose D 22 **456756**

 for suction hose D 27 **487071**

 for suction hose D 36 **487721**

Extraction adapter

D 50/D 36 AA

452897

Y-connector, antistatic

for D 50/D 36/D 27, with end cap for connection of two suction hoses

D 50 SV-AS/D 50 V

452898

End cap

 for closing the inlet nozzle, for retrofitting
CT 11/CTL, CT/CTL 22, CT/CTL 33, CT/CTL 44, CT/CTL 55

D 50/V

452899

Antistatic connecting sleeve

for connecting suction hoses D 50 / D 36 / D 27

D 50/D 50 VM-AS

493047
Tubes
Hand tube


Stainless steel, curved

D 36 HR-M

452900

 Polypropylene (PP); curved; with air regulator valve for
adjusting suction power

D 36 HR-K

452901

Extension pipe

Stainless steel, 3-piece, length: 950 mm

D 36 VR-M 3x

452902


Polypropylene (PP); 3-piece, length: 950 mm

D 36 VR-K 3x

452903


Anodised aluminium, 1-piece, length: 1,100 mm

D 50 VR-M

447599


Plastic 2-piece, length: 970 mm

D 50 VR-K 2x

440412

 Edited with the demo version of
Infix Pro PDF Editor

Extraction | Accessories

for CT mobile dust extractors and SR dust extractors

Type

Order No.

Floor nozzles



Industrial design, aluminium, with 2 castors and 2 brush inserts, width: 370 mm

D 36 BD 370

452908



Industrial design, aluminium, with 2 castors and 2 brush inserts, width: 450 mm

D 50 B D 450

452910



plastic, with 2 castors and 2 brush inserts, width: 300 mm

D 36 BD 300

452907



Plastic, with 2 castors and 2 brush inserts, width: 370 mm

D 50 BD 370

452909



4-piece, plastic, with 3 replacement inserts (brushes, rubber lips, carpet), width: 270 mm

D 36 BD 270

452906



Carpet nozzle
with sliding base, suitable for textiles or hard floors (switchable)

D 36 TD

452911



Turbo combination suction brush
for textile/hard floors, with 4 castors, brush rollers driven by intake air, width: 270 mm

D 36 TKB

450644

Special purpose nozzles/brushes



Crevice nozzle

Plastic, length: 300 mm

D 36 FD-300

452904

Plastic, length: 210 mm

D 36 FD-210

492391

Plastic, length: 200 mm

D 50 FD

452912



Suction brush

Plastic, diameter: 70 mm

D 36 SP

440404

Plastic, diameter: 85 mm

D 50 SP

440419



Upholstery nozzle

plastic, with brush insert, width: 120 mm

D 36 PD

440406



Universal brush nozzle

Plastic, circular brush, 120 x 40 mm

D 36 UBD

440403



Bevel-end nozzle

Rubber, length: 190 mm, diameter: 40 mm

D 36 SRD

411810



Flat nozzle

Special rubber, oil-resistant, width: 100 mm

D 36 FDG

440408



Edited with the demo version of
Infix Pro PDF Editor

To remove this notice, visit:
www.ieni.com/unlock.htm

for CT mobile dust extractors and SR dust extractors
Type**Order No.**
Cleaning sets

Nozzle cleaning set

Crevice nozzle D 36 FD-210, upholstery nozzle D 36 PD, suction brush D 36 SP, in a box

D 27/D 36 D-RS

492392
Standard cleaning set

Curved hand tube D 36 HR-K, 3 extension tubes D 36 VR-K, floor nozzle 4-piece D 36 BD270, crevice nozzle D 36 FD-210, upholstery nozzle D 36 PD, in a box

D 27/D 36 S-RS

492389
Professional cleaning set

Curved hand tube D 36 HR-M, 3-piece stainless steel extension tube D 36 VR-M3x, switchable floor nozzle D 36 TD, crevice nozzle D 36 FD-210, in a box

D 27/D 36 P-RS

492390
Compact cleaning set

Curved hand tube D 36 HR-K, 3 extension tubes D 36 VR-K, floor nozzle 4-piece D 36 BD270, crevice nozzle D 36 FD, upholstery nozzle D 36 PD, in a SYSTAINER

D 27/D 36 K-RS-Plus

456736
Cleaning set for craftsmen

Suction hose D 36 x 3,5 m-AS, curved hand tube D 36 HR-M, 3 extension tubes D 36 VR-M, carpet nozzle D 36 TD, crevice nozzle D 36 FD, upholstery nozzle D 36 PD, suction brush D 36 SP, in a SYSTAINER

D 36 HW-RS-Plus

454766
Workshop cleaning set

Suction hose D 36 x 3,5m-AS, curved hand tube D 36 HR-M, 3 extension tubes D 36 VR-M, floor nozzle D 36 BD370, in a SYSTAINER

D 36 WB-RS-Plus

454767
Universal cleaning set

Suction hose D 36 x 3,5 m-AS, curved hand tube D 36 HR-K, 3 extension tubes D 36 VR-K, carpet nozzle D 36 BD300, crevice nozzle D 36 FD, suction brush D 36 SP, upholstery nozzle D 36 PD, in a SYSTAINER

D 36 UNI-RS-Plus

454769
Heavy-duty cleaning set

Suction hose D 50 x 2,5 m, 2 extension tubes D 50 VR-K, floor nozzle D 50 BD370, square nozzle D 50 QD, suction brush D 50 SP, crevice nozzle D 50 FD, in a box

D 50 GS-RS

454770
Renovation cleaning set

1 curved hand tube D 36 HR-M, 3 extension tubes D 36 VR-M, 1 carpet nozzle D 36 TD, 1 crevice nozzle D 36 FD, 1 upholstery nozzle D 36 SP, in a SYSTAINER

D 36 RS-M-Plus

491804
Floor cleaning set

1 curved hand tube D 36 HR-M, 3 extension tubes D 36 VR-M, 1 floor nozzle D 36 BD 370, in a SYSTAINER

D 36 BD 370-RS-Plus

491965

A powerful solution for the workshop: the TURBO exhaust turbine from Festool.

It is the central component and the professional solution for the centralised dust extraction of several workplaces.



High pressure cleaning.
With the Jet-Air cleaning system, a rotating compressed air nozzle blows the filter out. This cleaning, which is carried out automatically on a cyclical basis, prevents the dust from caking and ensures a long filter service life.



Flexible power use.
Three versions of the exhaust turbines are available. They differ only in their suction power – their robust, technical design as well as their reliability in long term daily usage is identical.




Constant dust extraction.
Their high suction power makes it possible to remove sanding dust even over long tube distances. This provides an almost dust-free working environment, even if sanding is being carried on by several tools at the same time.



Simply clean.
The sanding dust that is drawn in is collected in the dust container. The dust can then be disposed of practically and conveniently with the plastic dust bag.





Extraction | Stationary



01
02
03
04
05
06

Exhaust turbines

TURBO 3091 and TURBO 4001

- High suction power during simultaneous use of several compressed air and electric tools via an AC drive that is stable during long term operation
- Simple and application-oriented operation
- Jet-Air cleaning system for the main filter

Exhaust turbines

TURBO 7501

- High suction power during simultaneous use of several compressed air and electric tools via an AC drive that is stable during long term operation
- Simple and application-oriented operation
- Jet-Air cleaning system for the main filter

Technical data

Connection voltage/frequency	400/50 V/Hz
Power consumption	
TURBO 3091	2.2 kW
TURBO 4001	3 kW
Compressed air supply	6 bar
Jet-Air cleaning (flow pressure) max.	
Flow volume max.	
TURBO 3091	4,670 l/m
TURBO 4001	4,833 l/m
Max. vacuum	28,000 Pa
Noise level	68 dB(A)
Dimensions (W x D x H) approx.	500 x 1,000 x 900 mm
Weight approx.	
TURBO 3091	107 kg
TURBO 4001	109 kg
Filter area	50,000 cm ²
Hose fitting supply/exhaust outside Ø	75 mm
Type of protection	54 IP
Parallel operation compressed air/electric tools	
TURBO 3091	2-3
TURBO 4001	3-4

Technical data

Connection voltage/frequency	400/50 V/Hz
Power consumption	5.5 kW
Compressed air supply	6 bar
Jet-Air cleaning (flow pressure) max.	
Flow volume max.	8,500 l/m
Max. vacuum	28,000 Pa
Noise level	74 dB(A)
Dimensions (W x D x H) approx.	600 x 1,100 x 1,200 mm
Weight approx.	200 kg
Filter area	50,000 cm ²
Hose fitting supply/exhaust outside Ø	75 mm
Type of protection	54 IP
Parallel operation compressed air/electric tools	5-6

Items included

TURBO 3091	273555
1 dust bag, 1 main filter (fitted)	
TURBO 4001	273394
1 dust bag, 1 main filter (fitted)	

Items included

TURBO 7501	273395
1 dust bag, 1 main filter (fitted)	

Accessories starting on page 68

Accessories starting on page 68



Extraction | Stationary extractor accessories

for turbines



Dust bags
Plastic, contents: 10 each

Type

Order No.

492730



Main filter
Filter surface area 50,000 cm²,
Degree of filtration 99.9%
Contents: 1 each

HF-TURBO

492731

Conversion kit
for converting Festool boom arms or energy boxes previously used with
mobile dust extractors, for automatic control of exhaust turbines TURBO
3091/4001/7501

UBS EAA/ASA TURBO

493562



IAS 2 connector with closing valve
for connecting IAS 2 suction hoses to central extraction units
Herkules system IAS 2-S-ZA/Herkules 490 605
Hamach/Rupes system

IAS 2-S-ZA/Herkules

490605

IAS 2-S-ZA/Hamach

490603



Edited with the demo version of
Infix Pro PDF Editor

To remove this notice, visit:
www.i-eni.com/unlock.htm

Extraction | Toolcenter with accessories



Toolcenter TC 3000

- Ergonomic layout of sanding workplaces
- Mobile storage of all sanding equipment
- Extractor dock for safe integration of the mobile dust extractor
- Transports equipment between different locations in the workshop – steering rollers provide maximum mobility
- Equipment always within easy reach
- Perfect organisation, safe supply lines (hose holder)
- Timesaving work organisation
- Lockable cabinet for tool storage

Technical data

Dimensions (Lx W x H)	470 x 1,070 x 960 mm
Storage area	460 x 990 mm
Work height	925 mm
Weight	43 kg

Items included

Order No.
583285





Accessories for Toolcenter

	Supply unit for compressed air supply to mobile dust extractors CTL, CTM 22/33 and Series SR 151, SR 200 dust extractors in LE versions, in a box	VE-TC 3000	454808
	Rear wall includes 10 hooks for hanging Dimensions: length x width 990 x 340 mm	TC 3000 RW	452986
	Hose holder for retrofitting	TC-SH	487304
	Tool holder for safe, ergonomic storage of up to two electric or compressed air tools at the same time	WHR/D-TC	493415
	Strap for securing Series SR 200 dust extractors	TC-SG-SR	454776
	Securing bracket for retrofitting, for securing mobile extractors CTL 22/33, CTM 22/33	TC-FB	454773



01
02
03
04
05
06





A black and white photograph showing a person's hands and lower torso as they use a Festool orbital sander on a dark, curved wooden surface. The lighting is dramatic, highlighting the texture of the wood and the tool.

Workplace equipment for efficient results.

A perfectly designed workplace reduces set-up and transit times and ensures that efforts will be employed in a targeted manner. For this reason, Festool optimises and develops equipment for working not only individually but also develops entire systems for the workplace. For faster, better and safer work. And for effective results!

04

Workplace equipment | The Festool system

	Dust extraction	Energy box	Installation options
Mobile extraction	 <p>CT dust extractor</p>	 <p>EAA EW CT/SR/M</p> <p>1</p>  <p>EAA EW/DW CT/SR/M</p> <p>2</p>	 <p>ASA 2500 CT/SR</p>  <p>ASA 5000 CT/SR ASA 6000 CT/SR</p>
Stationary extraction	 <p>TURBO exhaust turbine</p>	 <p>EAA EW TURBO/M</p> <p>1</p>  <p>EAA EW/DW TURBO/M</p>	 <p>EAA-W Wall mounting</p>  <p>EAA-D Ceiling installation</p>

3 EAA EW/DW TURBO/A

Electric tool (EW)

Compressed air tool (CA)

Edited with the demo version of
Infix Pro PDF Editor



Accessories

Tool

**Upgrades**

- 1** An upgrade from EW to EW/DW is possible with the VE2-EAA compressed air supply unit (see page 80).
- 2** An upgrade from the CT mobile dust extractor to the TURBO exhaust turbine is possible by removal of the forced guidance for the valve.
- 3** An upgrade from the manual valve to the automatic valve is possible (required: EW/DW variants) with the UBS-EAA-MA assembly kit (see page 80).



Edited with the demo version of
Infix Pro PDF Editor

To remove this notice, visit:
www.iceni.com/unlock.htm

Workplace equipment | Simply intelligent

The energy box from Festool: thought out in every detail

AUTOMATIC² ■■■■

The Festool automatic valve for perfect suction power – every time:

- Optimal turbine use and suction power at every workplace: because of the automatic valves, the valves are only opened when a tool is being used
- The valves open and close automatically when the tools are switched on and off¹⁾ – for efficient, timesaving work
- The speed of the automatic valve controller is ≈ 0.2 sec for opening/closing (actuated by pneumatic cylinders)
- Complete dust extraction by the hose system is guaranteed at all times




Automatic On/Off switch for extractors or turbines



- "Manual" and "Automatic" settings may be freely selected at every energy box
- For manual switching (switch position on "MAN"), the extractor or the turbine starts immediately
- For automatic switching (switch position on "AUTO"), the extractor or turbine starts automatically when the tool is switched on¹⁾

¹⁾ Electric and/or using compressed air, depending upon the EW or EW/DW version.



**Lightweight and stable.**


The cross section shows the stable interior. The structure of the profile provides the light aluminium boom arm with stability and high torsional rigidity. The smooth-walled extraction channel integrated in the profile prevents dust deposits.

**Robust.**

The double jointed boom is extremely robust and moves smoothly.

**Installation variants.**

Besides installation with the boom arm, it is now possible to install the energy box on a wall or ceiling. (Image: ceiling installation)

**Flexible and tidy.**

The energy box may be installed at any height and, because of the integrated cable retraction mechanism, the cable does not need to be shortened. The cable guide securely holds the cable: nothing gets twisted, nothing gets damaged.

**Optimal energy supply.**

Electric outlets:
1x constant voltage
2x automatic On switch for dust extraction
Compressed air connection:
EW/DW: 3x quick-couplings (2x lubricated, 1x non-lubricated)
EW: 1x quick-coupling (non-lubricated)

In addition: IAS connector is secured against falling off.

**Secure against tipping over.**

Electric and compressed air tools can be mounted in a stable manner that is secure against tipping over by using two tool hooks.

**Practical.**

There is a hose holder and integrated storage for abrasives on the back side.

Workplace equipment | CT/SR variants



**Energy box
EAA CT/SR (manual)**

- For use with Festool CT/SR mobile dust extractors
- Always ready for use with up to 2 electric and/or compressed air tools¹⁾
- Opening of the extraction channel via manual valve (simultaneous dust extraction by both tools is not possible)
- Integrated automatic On/Off switch for dust extraction as well as for electric and compressed air tools¹⁾
- Minimises set-up costs; increases economic efficiency
- Upgrade to the Turbo variant is possible
- Integrated power, compressed air and vacuum connections

¹⁾ Depending upon the EW/DW version.

**Boom arm
ASA 2500 CT/SR**

- For use with Festool CT/SR mobile dust extractors
- Pivoting boom arm with wall bracket
- Including a cable duct below the mobile dust extractor
- Expands the working area to 9 m²
- Saves time, space and increases economic efficiency
- Maximum flexibility, extra safety, no tripping hazards
- Ergonomic and flexible design of workplaces
- Installation on a wall or pillar possible



Technical data

Total height (without tube)	50 cm
Weight	EAA EW CT/SR/M EAA EW/DW CT/SR/M
Pressure range	4-8 bar

Technical data

Boom extension	2.5 m
Pivot range	9 m ²
Weight approx.	40 kg
Connecting line length	3 m

Items included

EAA EW CT/SR/M-EU Energy box with 3 x 230 V connections 1x DL (non-lubricated), manual valve actuation	583820
EAA EW/DW CT/SR/M-EU Energy box with 3x 230 V connections and complete compressed air supply unit with 3 DL connectors, manual valve actuation	583821

Accessories starting on page 80

Items included

ASA 2500 CT/SR-EU Pivoting arm with wall bracket and cable duct	583866
---	---------------

Accessories starting on page 80





Boom arm ASA 5000 CT/SR and ASA 6000 CT/SR

- For use with Festool CT/SR mobile dust extractors
- Including a cable duct below the mobile dust extractor
- Expands the working area to 39 m²-58 m²
- Saves time, space and increases economic efficiency
- Maximum flexibility, extra safety, no tripping hazards
- Ergonomic and flexible design of workplaces
- Installation on a wall or pillar possible




Technical data


Boom extension	ASA 5000 CT/SR	2x 2.5 m
	ASA 6000 CT/SR	2x 3.0 m
Pivot range	ASA 5000 CT/SR	39 m ² -58 m ²
	ASA 6000 CT/SR	56 m ² -84 m ²
Weight approx.	ASA 5000 CT/SR	72 kg
	ASA 6000 CT/SR	78 kg
Connecting line length		3 m

Items included	Order No.
ASA 5000 CT/SR-EU Double jointed boom with wall bracket and cable duct	583867
ASA 6000 CT/SR-EU Double jointed boom with wall bracket and cable duct	583868

Accessories starting on page 80



Workplace equipment | TURBO variants



**Energy box
EAA TURBO (manual)**

- For use with Festool TURBO exhaust turbines
- Manual valve actuation
- Always ready for use by up to 2 electric and/or compressed air tools¹⁾
- Opening of the extraction channel via manual valve (simultaneous dust extraction by both tools is not possible)
- Integrated automatic On/Off switch for dust extraction as well as for electric and compressed air tools¹⁾
- Minimises set-up costs; increases economic efficiency
- Upgrade to Turbo automatic is possible
- Integrated power, compressed air and vacuum connections

¹⁾ Depending upon the EW/DW version.

**Energy box
EAA TURBO (automatic)**

- For use with Festool TURBO exhaust turbines
- Automatic valve control of the extraction ports
- Always ready for use by up to 2 electric and/or compressed air tools¹⁾
- Opening of the extraction channel via automatic valve (simultaneous dust extraction by both tools is not possible)
- Integrated automatic On/Off switch for dust extraction as well as for electric and compressed air tools¹⁾
- Minimises set-up costs; increases economic efficiency
- Integrated power, compressed air and vacuum connections
- Only available in the EW/DW version



Technical data

Total height (without tube)	50 cm
Weight	13.0 kg
Pressure range	4-8 bar



Technical data

Total height (without tube)	50 cm
Weight	13.8 kg
Pressure range	4-8 bar

Items included

EAA EW TURBO/M-EU Energy box with 3x 230 V connections, 1x DL (non-lubricated), manual valve actuation	583810
EAA EW/DW TURBO/M-EU Energy box with 3x 230 V connections and complete compressed air supply unit with 3 DL connectors, manual valve actuation	583811

Order No.

Items included

EAA EW/DW TURBO/A-EU Energy box with 3x 230 V connections and complete compressed air supply unit with 3 DL connectors, automatic valve control	583831
---	---------------

Order No.

Accessories starting on page 80

Accessories starting on page 80





Boom arm ASA 5000 TURBO and ASA 6000 TURBO

- For use with Festool TURBO exhaust turbines
- Double-jointed arm with wall bracket
- Expands the working area from 39–84 m²
- Extraction connector above tube system
- Saves time, space and increases economic efficiency
- Maximum flexibility, extra safety, no tripping hazards
- Ergonomic and flexible design of workplaces
- Installation on a wall or pillar possible



Technical data

Boom extension	ASA 5000 TURBO	2x 2.5 m
	ASA 6000 TURBO	2x 3.0 m
Pivot range	ASA 5000 TURBO	39 m ² –58 m ²
	ASA 6000 TURBO	56 m ² –84 m ²
Weight approx.	ASA 5000 TURBO	72 kg
	ASA 6000 TURBO	78 kg
Connecting line length		3 m

Items included	Order No.
ASA 5000 TURBO-EU	583856
Double-jointed arm with wall bracket	
ASA 6000 TURBO-EU	583857
Double-jointed arm with wall bracket	

Accessories starting on page 80



Workplace equipment | Accessories

for boom arms

	Type	Order No.
Supply unit (upgrade and retrofit)		
for energy box upgrades (starting with 2009 models) of the EW type (only electric tools) to the EW/DW type for the combined operation of electric and compressed air tools, in a box Items included: compressed air module, maintenance unit, cable harness (electrical), pneumatic hoses	VE 2-EAA	495892
	VE 1-ASA	488508
Conversion kit for upgrading energy boxes (starting with the 2009 models) with manual valves to energy boxes with automatic valves Items included: floor group (separate valves, actuated by pneumatic cylinders), pneumatic solenoid valve, electric cable harness	UBS EAA-MA	495891
Conversion kit for converting Festool boom arms or energy boxes (models up to 2008) that have been used with mobile dust extractors, for automatic control of exhaust turbines TURBO 3091/4001/7501	UBS EAA/ASA TURBO	493562

IAS 2 connectors/ connecting sleeves / adapters

	IAS 2 connectors for connecting IAS 2 hoses, integrated connection for compressed air supply via the compressed air connection hose, antistatic version for the SRM 45, SRM 70, CT mobile dust extractors, LE versions, for EAA in the EW/DW version, in a box	IAS 2-A-ASA/CT/SRM45/70	454757
	IAS 2 connectors with closing valves for connecting IAS 2 suction hoses to central extraction units Herkules system	IAS 2-S-ZA/Herkules	490605
	Hamach/Rupes system	IAS 2-S-ZA/Hamach	490603
	Connecting sleeve for connecting from IAS 2 compressed air tools through an IAS 2 connection to central extraction units, aluminium, can be adapted to the particular central extraction unit by cutting, Ø 58 mm	IAS 2-AK	488416
	to energy boxes by Herkules, outside Ø 48 mm	IAS 2-FA	488417
	Rubber sleeve for connecting IAS 2 compressed air tools via an IAS 2 connection, for central extraction units, boom arms manufactured by Rupes, IVO and Herkules, as well as Rupes energy boxes	IAS 2-ZA	489222

Mounting kits

	Wall mounting kit Attachment brackets for wall mounting of energy boxes (for models starting in 2009) Items included: cable kit 4 m, compressed air hose 4 m, aluminium tube with connection sleeve, mounting kit for energy box	EAA-W	495889
	Bracket for ceiling installation of energy boxes Items included: cable kit 2.5 m, compressed air hose 2.5 m, holder	EAA-D	495890

for boom arms**Type****Order No.****Suction hoses for compressed air tools****IAS 2 antistatic hose¹⁾**

Temperature resistant to +70°C in accordance with DIN IEC 312, leakage resistance ≤ 10 MΩ, in a box

Length: 3.5 m	IAS 2-3500 AS	487901
Length: 5 m	IAS 2-5000 AS	488176
Length: 7 m Note: not for the combination of CT/SR plus ASA	IAS 2-7000 AS	488131
Length: 10 m Note: not for the combination of CT/SR plus ASA	IAS 2-10000 AS	494006
Length: 15 m Note: not for the combination of CT/SR plus ASA	IAS 2-15000 AS	494528

**IAS 2 non-antistatic hose**

Temperature resistant up to +70°C, in a box

Length: 3.5 m	IAS 2-3500	488132
Length: 5 m	IAS 2-5000	488175
Length: 7 m Note: not for the combination of CT/SR plus ASA	IAS 2-7000	488133

¹⁾ The antistatic function is only guaranteed for dust extractors that have antistatic equipment.**Suction hoses for electric tools****Antistatic suction hose¹⁾**

Temperature resistant to +70°C, in accordance with DIN IEC 312

Leakage resistance ≤ 10 MΩ, in a box

With rotating adapter and connection sleeve, length: 3.5 m	D 27x3,5m-AS	452878
With rotating adapter and connection sleeve, length: 5 m	D 27x5m-AS	452880
Special design only for SRM 312 LE-AS/ SRM 70 LE-EC, with angular rotating adapter and connection sleeve, length: 3.5 m	D 27x3,5m-AS/B1	489266



With plug it connector, length: 3.5 m

plug it D 27x3,5m-AS

456746**Non-antistatic suction hose**

Temperature resistant up to +70°C, in a box

With rotating adapter and connection sleeve, length: 3.5 m	D 27x3,5m	452877
With rotating adapter and connection sleeve, length: 5 m	D 27x5m	452879







Cordless drills to meet any challenge.

Festool cordless drills combine unsurpassed convenience with outstanding power and the greatest durability. They incorporate brushless EC motors of exceptional efficiency. The intelligent motor management always lets them control the force that they generate. Versatile accessories adapt to all types of drilling and fastener driving applications. Together, Festool battery operated tools are ideal partners for the challenges that you face every day.

05

Drilling and screwdriving | The Festool system

Cordless drills

Sets, battery packs and chargers



Cordless drill **C 12**



Cordless drills **T 12+3 / T 15+3**



Tool chuck
CENTROTEC



Eccentric adapter
FastFix



Compact battery pack
BPS 12 C NiMH



Standard battery pack
BPS 12 S NiMH



Standard battery pack
BPS 15,6 S NiMH



Lithium-ion battery pack (Li)
BPS 12 Li
BPS 15 Li

01
02
03
04
05
06

Screwdriver and drill bits

Elbow adapter
FastFixKeyless chuck
FastFix

Bits



Bit holder



HSS twist drill



Adapter for sockets

Rapid charger
for all Festool battery packs
NiCd, NiMH and lithium-ionRapid charger
for all Festool battery packs
NiCd and NiMH

SYSTAINER

Drilling and screwdriving | Cordless Drills



Cordless drills **T 12+3** and **T 15+3**

- Brushless EC-TEC motor with integrated motor management for a long service life and the greatest power
- Impressive ergonomics: compact, lightweight and perfectly balanced
- Fully electronic torque setting and switching for precise screwdriving
- Switching from screwdriving to drilling without changing the set torque value
- FastFix interface for all FastFix attachments and CENTROTEC rapid tool-change system
- Lightweight, powerful and always ready for use with the latest lithium-ion rechargeable battery technology



Technical data **T 12+3**

Battery voltage	Li-ion NiMH	10.8 V 12 V
Idling speed, 1st gear/2nd gear		0-450 / 0-1,500 rpm
Drilling diameter, wood/steel		25/14 mm
Torque setting		0.5-8 Nm
Max. torque, wood/steel		22/30 Nm
Chuck range		1.5-13 mm
Battery capacity/ charging time approx.		2.6 Ah Li-ion/45 min 2.0 Ah NiMH/45 min
Weight with lithium-ion battery		1.4 kg

Technical data **T 15+3**

Battery voltage	Li-ion NiMH	14.4 V 15.6 V
Idling speed, 1st gear/2nd gear		0-450 / 0-1,500 rpm
Drilling diameter, wood/steel		35/16 mm
Torque setting		0.5-8 Nm
Max. torque, wood/steel		27/40 Nm
Chuck range		1.5-13 mm
Battery capacity/ charging time approx.		2.6 Ah Li-ion/45 min 3.0 Ah NiMH/60 min
Weight with lithium-ion battery		1.5 kg

Items included **T 12+3**

Charger TRC 3, tool chuck CENTROTEC, twist drill D4 CENTROTEC, bit holder CENTROTEC, FastFix chuck 13 mm, bit PZ 2	Order No.
T 12+3 Li 2.6 Set FastFix elbow adapter, FastFix eccentric adapter, 2nd battery pack S Li-ion 2.6 Ah, in a SYS 1 SYSTAINER	564231
T 12+3 Li 2.6 Plus 2nd battery pack S Li-ion 2.6 Ah, in a SYS 1 SYSTAINER	564214
T 12+3 MH 2.0 Set FastFix elbow adapter, FastFix eccentric adapter, 2nd battery pack C NiMH 2.0 Ah, in a SYS 1 SYSTAINER	564229
T 12+3 MH 2.0 Plus 2nd battery pack C NiMH 2.0 Ah, in a SYS 1 SYSTAINER	564206

Accessories starting on page 88

Items included **T 15+3**

Charger TRC 3, tool chuck CENTROTEC, twist drill D4 CENTROTEC, bit holder CENTROTEC, FastFix chuck 13 mm, bit PZ 2	Order No.
T 15+3 Li 2.6 Set FastFix elbow adapter, FastFix eccentric adapter, 2nd battery pack S Li-ion 2.6 Ah, in a SYS 1 SYSTAINER	564235
T 15+3 Li 2.6 Plus 2nd battery pack S Li-ion 2.6 Ah, in a SYS 1 SYSTAINER	564225
T 15+3 MH 3.0 Set FastFix elbow adapter, FastFix eccentric adapter, 2nd battery pack C NiMH 3.0 Ah, in a SYS 1 SYSTAINER	564221
T 15+3 MH 3.0 Plus 2nd battery pack C NiMH 3.0 Ah, in a SYS 1 SYSTAINER	564221

Accessories starting on page 88





Cordless drill C 12

- Brushless EC-TEC motor for a long service life and maximum efficiency
- Ultra-light weight and the highest screwdriving power
- Impressive ergonomics: compact, lightweight and perfectly balanced
- FastFix interface for all FastFix attachments and the CENTROTEC rapid tool-change system



Technical data

Battery voltage	12 V
Idling speed, 1st gear/2nd gear	0-450 / 0-1,500 rpm
Drilling diameter, wood/steel	25/14 mm
Torque setting 1st/2nd gear	2-7/0.5-2.5 Nm
Max. torque, wood/steel	18/30 Nm
Chuck range	1-13 mm
Battery capacity/ charging time approx.	2.0 Ah C NiMH/40 min 3.0 Ah S NiMH/70 min
Weight with C NiMH	1.5 kg

Items included

Order No.

Charger LC 45, tool chuck CENTROTEC, twist drill D4 CENTROTEC, bit holder CENTROTEC, FastFix chuck 13 mm, bit PZ 2	
C 12 CE-MH45 Set	564167
FastFix elbow adapter, FastFix eccentric adapter, 2nd battery pack S NiMH 3.0 Ah, in a SYS 1 SYSTAINER	
C 12 CE-MH45-Plus	564165
2nd battery pack S NiMH 3.0 Ah, in a SYS 1 SYSTAINER	
C 12 CE-MH-C45-Set	564245
FastFix elbow adapter, FastFix eccentric adapter, 2nd battery pack C NiMH 2.0 Ah, in a SYS 1 SYSTAINER	
C 12 CE-MH-C45-Plus	564241
2nd battery pack C NiMH 2.0 Ah, in a SYS 1 SYSTAINER	

Accessories starting on page 88




When the space is small, the C 12 shows its real size!

Because of the FastFix attachments, it fits perfectly into every type of work situation.

With this set version, you will always have everything at your finger tips – properly stored in a SYSTAINER:

- | Charger LC 45
- | CENTROTEC tool chuck
- | Twist drill bit D4 CENTROTEC
- | CENTROTEC bit holder
- | FastFix keyless chuck 13 mm
- | PZ 2 bit
- | FastFix angle attachment
- | FastFix eccentric attachment
- | 2nd battery pack

Drilling and screwdriving | Accessories



Battery packs

	Type	Order No.
Lithium-ion (Li) Voltage: 10.8 V Capacity: 2.6 Ah Weight: 470 g	BPS 12 Li	494831
Nickel metal hydride (NiMH) Voltage: 12 V Capacity: 2.0 Ah Weight: 570 g	BPS 12 C NiMH	491825
Voltage: 12 V Capacity: 3.0 Ah Weight: 760 g	BPS 12 S NiMH	491821
Nickel cadmium (NiCd) Voltage: 12 V Capacity: 1.3 Ah Weight: 560 g	BPS 12 C NiCd	493348
Voltage: 12 V Capacity: 2.4 Ah Weight: 760 g	BPS 12 S NiCd	492268
Lithium-ion (Li) Voltage: 14.4 V Capacity: 2.6 Ah Weight: 560 g	BPS 15 Li	494832
Nickel metal hydride (NiMH) Voltage: 15.6 V Capacity: 3.0 Ah Weight: 940 g	BPS 15,6 S NiMH	491823
Nickel cadmium (NiCd) Voltage: 15.6 V Capacity: 2.4 Ah Weight: 940 g	BPS 15,6 S NiCd	492269

Keyless chuck and adapters

for all Festool cordless drills with FastFix interfaces

	CENTROTEC tool chuck	WH-CE CENTROTEC	492135
	FastFix keyless chuck For clamping drill bits and other bits without the use of tools		
	Chuck capacity 1.5-13 mm	BF-FX 13 FastFix	490698
	Chuck capacity 1-10 mm	BF-FX 10 FastFix	491350
	FastFix angle attachment	DD-AS	490293
	FastFix eccentric attachment	DD-ES	490294

Edited with the demo version of
Infix Pro PDF Editor

To remove this notice, visit:
www.iceni.com/unlock.htm



	Type	Order No.
Quick charger		
	for all Festool battery packs NiCd, NiMH and Li	TRC 3 494676
	for all Festool battery packs NiCd and NiMH	LC 45 491820

Standard drill bit selection


Novadrive HSS twist drills

polished in accordance with DIN 338

Diameter: 1 mm, package contents: 10 each	HSS D 1/10	492541
Diameter: 1.5 mm, package contents: 10 each	HSS D 1,5/10	492542
Diameter: 2 mm, package contents: 10 each	HSS D 2/10	492543
Diameter: 2.5 mm, package contents: 10 each	HSS D 2,5/10	492544
Diameter: 3 mm, package contents: 10 each	HSS D 3/10	492545
Diameter: 3.5 mm, package contents: 10 each	HSS D 3,5/10	492546
Diameter: 4 mm, package contents: 10 each	HSS D 4/10	492547
Diameter: 4.5 mm, package contents: 10 each	HSS D 4,5/10	492548
Diameter: 5 mm, package contents: 10 each	HSS D 5/10	492549
Diameter: 5.5 mm, package contents: 10 each	HSS D 5,5/10	492550
Diameter: 6 mm, package contents: 10 each	HSS D 6/10	492551
Diameter: 6.5 mm, package contents: 10 each	HSS D 6,5/10	492552
Diameter: 7 mm, package contents: 10 each	HSS D 7/10	492553
Diameter: 7.5 mm, package contents: 10 each	HSS D 7,5/10	492554
Diameter: 8 mm, package contents: 10 each	HSS D 8/10	492555
Diameter: 8.5 mm, package contents: 10 each	HSS D 8,5/10	492556
Diameter: 9 mm, package contents: 10 each	HSS D 9/10	492557
Diameter: 9.5 mm, package contents: 10 each	HSS D 9,5/10	492558
Diameter: 10 mm, package contents: 10 each	HSS D 10/10	492559
Novadrive metal drill bit case 19 pieces, diameter: 1-10 mm	SBKS-HSS D 1-10	492560



CENTROTEC tool selection: bits and bit holders


CENTROTEC Pozidriv HiQ bits, 100 mm

Size: PZ 1, package contents: 2 each	HiQ PZ 1-100 CE/2	492527
Size: PZ 2, package contents: 2 each	HiQ PZ 2-100 CE/2	492528
Size: PZ 3, package contents: 2 each	HiQ PZ 3-100 CE/2	492529


CENTROTEC Phillips bits, 100 mm

Size: PH 1, package contents: 2 each	HiQ PH 1-100 CE/2	492530
Size: PH 2, package contents: 2 each	HiQ PH 2-100 CE/2	492531
Size: PH 3, package contents: 2 each	HiQ PH 3-100 CE/2	492532


CENTROTEC Torx bits, 100 mm

Size: TX 15, package contents: 2 each	HiQ TX 15-100 CE/2	492533
Size: TX 20, package contents: 2 each	HiQ TX 20-100 CE/2	492534
Size: TX 25, package contents: 2 each	HiQ TX 25-100 CE/2	492535
Size: TX 30, package contents: 2 each	HiQ TX 30-100 CE/2	492536


 Edited with the demo version of
 Infix Pro PDF Editor

Drilling and screwdriving | Accessories

	Type	Order No.
CENTROTEC tool selection: bits and bit holders		
	Bit box, contents: 10 pieces 2x PZ 1, 5x PZ 2, 2x PZ 3, CENTROTEC magnetic bit holder BH 60 CE	POZIDRIV + BH 60-CE 493260
	1x TX 10, 2x TX 15, 3x TX 20, 2x TX 25, 1x TX 30, CENTROTEC magnetic bit holder BH 60 CE	TORX + BH 60-CE 493261
	PH 1, PH 2, PZ 1, PZ 2, PZ 3, TX 15, TX 20, TX 25, SZ 0,8x55, CENTROTEC magnetic bit holder BH 60 CE	MIX + BH 60-CE 493262
	CENTROTEC quick-change bit holder Package contents: 1 each	BHS 65 CE 492648
	CENTROTEC magnetic bit holder Package contents: 1 each	BH 60 CE 492539
	CENTROTEC extra long magnetic bit holder 150 mm, package contents: 1 each	BV 150 CE 492540
	CENTROTEC socket adapters With ball retainer for manual operation With pin retainer for machine operation With ball retainer for manual operation With pin retainer for machine operation	1/4"-50 CE/KG CENTROTEC 495131 1/4"-50 CE/ST CENTROTEC 495132 3/8"-70 CE/KG CENTROTEC 495133 3/8"-70 CE/ST CENTROTEC 495134
	CENTROTEC screwdriver handle	CENTROTEC-DRIVE 495228
	CENTROTEC Pozidriv HiQ bits, 25 mm Size: PZ 1, package contents: 3 each Size: PZ 2, package contents: 3 each Size: PZ 3, package contents: 3 each Size: PZ 4, package contents: 3 each	HiQ PZ 1-25 /3 490471 HiQ PZ 2-25 /3 490472 HiQ PZ 3-25 /3 490473 HiQ PZ 4-25 /3 490474
	Pozidriv AQ bits, 25 mm Size: PZ 1, package contents: 3 each Size: PZ 2, package contents: 3 each Size: PZ 3, package contents: 3 each	PZ 1-25 /10 490481 PZ 2-25 /10 490482 PZ 3-25 /10 490483
	Phillips HiQ bits, 25 mm Size: PH 1, package contents: 3 each Size: PH 2, package contents: 3 each Size: PH 3, package contents: 3 each	HiQ PH 1-25 /3 490491 HiQ PH 2-25 /3 490492 HiQ PH 3-25 /3 490493
	Phillips AQ bits, 25 mm Size: PH 1, package contents: 10 each Size: PH 2, package contents: 10 each Size: PH 3, package contents: 10 each	PH 1-25 /10 490501 PH 2-25 /10 490502 PH 3-25 /10 490503
	Slotted AQ bits, 25 mm Size: SZ 0,6 x 4,5, package contents: 10 each Size: SZ 0,8 x 5,5, package contents: 10 each Size: SZ 1,2 x 6,5, package contents: 10 each	SZ 0,6x4,5-25/10 493309 SZ 0,8x5,5-25/10 493310 SZ 1,2x6,5-25/10 493311
	Torx HiQ bits, 25 mm Size: TX 10, package contents: 3 each Size: TX 15, package contents: 3 each Size: TX 20, package contents: 3 each Size: TX 25, package contents: 3 each Size: TX 30, package contents: 3 each Size: TX 40, package contents: 3 each	HiQ TX 10-25 /3 490494 HiQ TX 15-25 /3 490495 HiQ TX 20-25 /3 490496 HiQ TX 25-25 /3 490497 HiQ TX 30-25 /3 490498 HiQ TX 40-25 /3 490499
	Torx TX Bits, 25 mm Size: TX 10, package contents: 3 each Size: TX 15, package contents: 3 each Size: TX 20, package contents: 3 each Size: TX 25, package contents: 3 each Size: TX 30, package contents: 3 each	TX 10-25 /3 490504 TX 15-25 /3 490505 TX 20-25 /3 490506 TX 25-25 /3 490507 TX 30-25 /3 490508

Edited with the demo version of
Infix Pro PDF Editor



Versatility that can't be beat – Festool cordless drills.

Whether it has to do with installing parts on a vehicle or spot repairs, a Festool cordless drill with its 4 system adapters is the ideal tool system for all installation work before and after painting.



Extremely versatile.
Thanks to the FastFix interface, the CENTROTEC tool chuck and all other accessories can be changed in an instant. And this will save you valuable time.



Screwdriving easily around corners.
By using the FastFix elbow adapter, you will now very easily be able to even reach screws that are hidden.



Working close to the edges.
Working close to edges made easy: with the FastFix eccentric adapter, the screws sit perfectly on the edge.



A comprehensive range of accessories.
Festool cordless drills perform even mobile polishing tasks simply brilliantly.



Motors that last.
Enormous power, light weight, a long service life and maximum durability.



FastFix eccentric attachment
FastFix chuck
CENTROTEC tool chuck
FastFix angle attachment





SYSTAINER and SORTAINER for systematic organising.

Making your work easier - that is always the focus of what we do. A good example of this is the flexible organising system from Festool that organises, stores and transports your tools and accessories, everything together in a single system. Using the Festool system, you will always have everything that you will ever need right at your fingertips. This will save you time and will guarantee that your customers look upon you as a professional. One of the big advantages to being systematically organised.

06



Organisation with a system – Festool SYSTAINER, SORTAINER and Systainer-Ports.

Everything really finds its right place in a Festool SYSTAINER: power tools, hand tools, accessories, small parts and anything else that you use in your work. Practical refinements provide unique advantages in your daily work.



Award winning.

The SYSTAINER is setting the standards for innovation, function and design, and has won several awards.

Fastening technology.

The locking latches close the lid and securely join two stacked SYSTAINER together.




Sterling performance.

Coupling several SYSTAINER to one another, to a CT mobile dust extractor or on a rolling base saves time and effort during assembly work.



Inserts and inlays.

The right insert for every part: different inlays and deep-drawn inserts keep everything tidy (available as accessories).



The rolling base.

Mobility at hand: the rolling base lets you move quickly from one location to the next, at your workplace or on a construction site (available as an accessory).



The Systainer-Port.

This mobile storage system can be adapted to SYSTAINER of any size. SYSTAINER and SORTAINER can be stored safely and save space at the same time. They can be stationary or mobile on wheels.



Pullout lock / individually locking.

These features prevent the drawers from being removed or falling out unintentionally.



Organisation on wheels with the Systainer-Port.

For the workshop: customised adaptation to heights of all SYSTAINER and SORTAINER, optimal utilisation of space.

SYSTAINER and SORTAINER

01
02
03
04
05
06

SYSTAINER

Type

Order No.

SYSTAINER without inlays


SYSTAINER SYS 1

Dimensions (L x B x H) 395 x 295 x 105 mm
Weight 1.4 kg

SYS 1

445433
SYSTAINER SYS 2

Dimensions (L x B x H) 395 x 295 x 157.5 mm
Weight 1.6 kg

SYS 2

445434
SYSTAINER SYS 3

Dimensions (L x B x H) 395 x 295 x 210 mm
Weight 1.6 kg

SYS 3

445596
SYSTAINER SYS 4

Dimensions (L x B x H) 395 x 295 x 315 mm
Weight 2.4 kg

SYS 4

445597
SYSTAINER SYS 5

Dimensions (L x B x H) 395 x 295 x 420 mm
Weight 3.0 kg

SYS 5

493283
Maxi-Systainer

for coupling with SORTAINER and SYS 1, SYS 2, SYS 3, SYS 4, and SYS 5

Dimensions (L x B x H) 590 x 390 x 210 mm
Weight 4.0 kg

SYS MAXI

490701

Dimensions (L x B x H) 590 x 390 x 157.5 mm
Weight 3.0 kg

SYS MAXI 2

492582
Mini-Systainer

not able to couple with SORTAINER or SYS 1, SYS 2, SYS 3, SYS 4 or SYS 5

Dimensions (L x B x H) 265 x 170 x 70 mm
Weight 0.4 kg

SYS MINI

460853

SYSTAINER and SORTAINER

SYSTAINER

SYSTAINER with inlays

SYSTAINER with inlays for Festool power tools



C 12, SYSTAINER size SYS 1	SYS-C 12	493532
RTS 400/RS 400, SYSTAINER size SYS 1	SYS-RTS 400/RS 400	489124
TDK, SYSTAINER size SYS 1	SYS-TDK	493275
ETS/ES 125, SYSTAINER size SYS 2	SYS-ETS/ES 125	489226
RAS 115, SYSTAINER size SYS 2	SYS-RAS 115	487784
RO 150, SYSTAINER size SYS 2	SYS-RO 150	487782
RS 100/RS 1, SYSTAINER size SYS 2	SYS-RS 100/RS 1	487184
RS 200/RS 2, SYSTAINER size SYS 2	SYS-RS 200/RS 2	487783
RS 300/RS 3, SYSTAINER size SYS 2	SYS-RS 300/RS 3	487226
ETS/ES 150, SYSTAINER size SYS 3	SYS-ETS/ES 150	489702
RO 150 FEQ, SYSTAINER size SYS 3	SYS-RO 150 FEQ	494640



SYSTAINER with inlays for abrasives



Abrasive Ø 115 mm, SYSTAINER size SYS 1	SYS-STF D 115	487432
Abrasive Ø 125 mm, SYSTAINER size SYS 1	SYS-STF D 125	489463
Abrasive 80 x 133 mm, SYSTAINER size SYS 1	SYS-STF 80x133	487435
Abrasive 115 x 228 mm, SYSTAINER size SYS 2	SYS-STF 115x228	487433
Abrasive 93 x 178 mm, SYSTAINER size SYS 2	SYS-STF 93x178/93V	487434
Abrasive Ø 150 mm, SYSTAINER size SYS 3	SYS-STF D 150	487431

SYSTAINER with universal inlays for small parts,
SYSTAINER size SYS 1

Type

Order No.

SYSTAINER with simple, foam grid insert to fit any desired shape, SYSTAINER size SYS 1	SYS 1 VARI	487410
SYSTAINER with simple, foam grid insert to fit any desired shape, SYSTAINER size SYS 2	SYS 2 VARI	487485



SYSTAINER with pre-cut foam insert for tidy storage of D 8, D 12 milling tools, SYSTAINER size SYS 1	SYS-O/F D8/D12	487925
---	----------------	---------------




SYSTAINER with individual, removable plastic containers, SYSTAINER size SYS 1	SYS 1 BOX	487552
--	-----------	---------------



SYSTAINER

Type

Order No.

Inlays and inserts for *SYSTAINER***Insert box**

- for the SYS 1 BOX, red
Dimensions (L x B x H) 54 x 54 x 63 mm
Package contents: 12 each
- for the SYS 1 BOX, yellow
Dimensions (L x B x H) 108 x 54 x 63 mm
Package contents: 6 each
- for the SYS 1 BOX, blue
Dimensions (L x B x H) 108 x 108 x 63 mm
Package contents: 3 each
- for the SYS 1 BOX, green
Dimensions (L x B x H) 162 x 108 x 63 mm
Package contents: 2 each

BOX 54x54/12 SYS 1 **487657**BOX 108x54/6 SYS 1 **487658**BOX 108x108/3 SYS 1 **487659**BOX 162x108/2 SYS 1 **487660****Cover inlay**

- for the SYS 1 Box, rigid foam, flat

DE SYS 1-4 **491641****Cartridge insert**

- for the SYS 4 with telescoping frame or the SYS 5
for storing cartridges

TZE-KT SYS 4 **491639****SYSTAINER with insert for hand tools**

- Tools you require can be located quickly since all hand tools are clearly arranged for the carpenter/joiner, wood insert for tools included,
arrangement suggestion.
Systainer size SYS 4

SYS-HWZ **491301****Foam inserts for SYSTAINER****Foam inserts for SYS 1-5**

- Set with a dimpled insert (for lid), base insert and diced insert
Package contents: 3 each

SYS-VARI SE **487427****Foam grid set**

- for SYS 1-5, for fitting any desired shape, grid mat
Package contents: 2 each

SYS-VARI RM **487428****Base pad**

- for SYS 1-5

SE-BP SYS 1-5 **491642**

- for the SYS MAXI

SE-BP SYS-MAXI **491632****Lid pad**

- for the SYS MINI, dimpled

SE-DP SYS-MINI **491638**

- for SYS 1-5, dimpled

SE-DP SYS 1-5 **491640**

- for the SYS MAXI, dimpled

SE-DP SYS-MAXI **491633****Universal inlays and deep-drawn inserts**

- Universal inlays for the SYS MINI

TZE-UNI SYS-MINI **491634**

- Deep-drawn insert with 6 compartments, for the SYS MINI

TZE-6 SYS-MINI **491635**

- Deep-drawn insert with 5 compartments, for the SYS MINI

TZE-5 SYS-MINI **491636**

- Deep-drawn insert with 3 compartments, for the SYS MINI

TZE-3 SYS-MINI **491637**

SYSTAINER and SORTAINER

SORTAINER

Variants

	Type	Order No.
	SYS 3-SORT/4	491522
	SYS 3-SORT/6	491984
	SYS 3-SORT/9	491985
	SYS 3-SORT/12	491986

Other accessories

	Telescoping frame Frame, dimensions (L x W x H) 395 x 295 x 107 mm, for elevating the SYS 4 to 422 mm	TKR-SYS	491631
	Tool cover for SYS 1 - 4, tools not included	WZD-SYS	491643
	Rolling base for transporting SYSTAINER in sizes 1-5 and SORTAINER, with 4 ball bearing-mounted steering rollers and locking brake, max. load 50 kg	RB SYS 1-5	492388

Systainer-Ports and Accessories


	Systainer-Port Sturdy sheet steel body 5 labels for drawers, with 5 SYSTAINER telescopic drawers, a set of castors, 4 steering rollers (2 with locking brakes), without SYSTAINER	SYS-PORT 1000/2	491922
	5 labels for drawers, with 3 SYSTAINER telescopic drawers, without SYSTAINER	SYS-PORT 500/2	491921
	Telescopic drawer 5 labels for drawers	SYS-PORT/TA/2	491923
	Set of castors for moving the Systainer-Port 4 steering rollers (2 of which can be locked)	SYS-PORT R/2	491932

Application Systainer

	SYSTAINER accessories 1x rotor, 4x vanes, 5x silencers, 5x Woodruff keys, 5x two clamps, gaskets and O-rings in various sizes	SYS-SERVICE LEX	489200
---	---	-----------------	---------------





A screenshot of a web browser window. The address bar shows the URL <http://www.festool-automotive.com>. The title bar of the browser says "Festool Automotive". The main content area of the browser displays the Festool Automotive website.

Just a click away: www.festool-automotive.com
Automotive products on the Internet.

Around the clock and around the world – you can find our entire product range along with a great deal of exciting information at www.festool-automotive.com. Just click on the address!

Clear. The online automotive catalogue with all the products, accessories, consumables and many applications.

Current. An overview of every interesting innovation as well as numerous tips and information.

Informative.

- Download section
- National and international references
- Application examples
- Dealer overview
- Service information
- and much more



Festool services

1 1+2 Warranty



2 Customer service



3 After-sales service



Not just 1 or 2, but 1 plus 2!

If used properly¹⁾, Festool guarantees its products for 2 years from the date of purchase. This guarantee will be extended for an additional year, for a total guarantee period of 3 years, if, within 30 days after the date of purchase, you fill out and send in the guarantee card that is included with your newly purchased product to Festool, or register online at www.festool.com/service.

Customer service like it should be:

Fast. Uncomplicated. Professional. 48 hour service: repairs will be performed or a cost estimate provided within 48 hours after the tool has arrived at our workshop. The pickup service: a courier service will pickup the consignment from you or your Festool dealer and bring it back to you once the tool has been repaired. We will absorb all costs if the item is under warranty. In the case of a repair which is invoiced, you only pay for transport costs one way.


Repairs made easy.

There are two options for repairs:

1. Handling through your dealer.
2. Contacting our central customer service directly.

The item can be sent directly and easily in a SYSTAINER.

The customer service address is given on the back of this catalogue.



Nothing can replace the original.

The same goes for replacement parts. You will find the necessary part number on the diagram included with each new product. Alternatively, search for the replacement part in the online replacement parts catalogue at www.festool.com. If an item is being ordered by your dealer, the tool type, base tool number and the tool number will also be required. This information may be found on the tool nameplate.

Certification in accordance with DIN ISO 9001 and DIN ISO 14001

We place the highest demands on our quality – and we will even provide you with evidence of this in writing: with the certificate of compliance in accordance with **DIN ISO 9001**. Festool was certified without any exceptions in an independent audit. And not only in production, but in all company departments – from development to purchasing, from customer service to logistics. And this seal of quality means one thing most of all: safety for you.

At the same time, however, this quality forms the basis of a positive environmental effort. Because the outstanding service life, the low rate of wear and the ability to repair Festool tools saves on raw materials and protects the environment. And this has also been officially certified since 2007 – in accordance with **DIN ISO 14001**.

¹⁾ Within the EU in accordance with the operating manual.

A – Z | Keywords

3 in 1	
ROTEX RO 150 .	8, 18, 39
ROTEX RO 125 .	8, 18, 40
1+2 Warranty.	100

A

Antistatic suction hose .	14
Accessories-Systainer LEX .	15, 98
Application Systainer:	
Compressed air service access..	15, 98
Abrasives	30
Application example:	
Polishing out holograms .	41
Polishing UV paints..	41
Aluminium sanding workplace .	53
ATEX directive 94/9/ECC (Type 22)/	
B1 SRM 70/B1 .	52
Aluminium sanding workplaces .	53
Air filter cassette .	62
Angular rotating adapter .	63
Antistatic connector sleeve .	63
Attachment bracket TC .	69
ASA 2500 CT/SR .	76
ASA 5000 CT/SR .	77
ASA 6000 CT/SR .	77
ASA 5000 TURBO .	79
ASA 6000 TURBO .	79
Adapters socket CENTROTEC .	90
After-sales service .	100

B

Brush insert RAS .	28
beige, fine .	44
black, very fine (honeycombed).	45
black, very fine (honeycombed).	45
Bevel-end nozzle .	64
Boom arm	
ASA 2500 CT/SR .	76
ASA 5000 CT/SR .	77
ASA 6000 CT/SR .	77
ASA 5000 TURBO .	79
ASA 6000 TURBO .	79
Bracket EAA .	80
Battery pack	
Lithium-ion (Li) .	84, 88
Nickel metal hydride (NiMH) .	84,
88	
Battery charger .	84, 89
Battery chargers .	84, 89
Bits	
Pozidriv .	85, 89, 90
Phillips .	85, 89, 90
Torx .	85, 89, 90
Slotted bits.	85, 89, 90
Bit holders .	85, 90
Bits and bit holders .	89, 90
Bit box .	90

C

Coarse sanding .	8
Compressed air orbital Sanders	
LRS 93 M .	8, 11
LRS 93 G .	8, 11
LRS 400 .	8, 11
Compressed air eccentric sander	
LEX 2 125/3 .	8, 12
LEX 2 125/7 .	8, 12
LEX 2 150/3 .	8, 12
LEX 2 150/7 .	8, 12
LEX 2 150/11 .	8, 13
LEX 2 185/7 .	8, 13
Compressed air tools .	11-13
Compressed air service unit .	14, 58, 59
Connecting sleeve .	15, 59, 80
Cleaning and lubricating oil .	15
Cup brush RAS .	28
Cristal - abrasive medium .	30-32
Ceramic high gloss polish .	42

CTL MIDI .	48, 50, 54/55
CTL MINI .	48, 50, 54/55
CTM 22-55 .	48, 51, 54/55
CTL 22-55 .	48, 51, 54/55
Compressed air module .	58
Connector sleeve .	63
Carpet nozzle .	64
Crevice nozzle .	64
Craftsman cleaning set .	65
Cleaning sets .	65
Compact cleaning set .	65
Compressed air service unit	
TC 3000 .	69
Compressed air service unit	
EAA, ASA .	80
Cordless drills	
The system .	84-85, 91
Cordless drills	
T 12+3 / T 15+3 .	84, 86
C 12 .	84, 87
CENTROTEC tool chuck .	84, 88
CENTROTEC tool selection .	89
CENTROTEC screwdriver handle .	90
Cartridge insert SYS .	97
Castor set SYS-PORT .	98
Customer service .	100
Customer club .	101, 106

D

Dry sanding system .	8-9
Dead man's switch..	12, 13
Dust extraction (stationary)	
TURBO 3091 .	48, 67
TURBO 4001 .	48, 67
TURBO 7501 .	48, 67
Dust extraction - the system .	48-49
Dust explosion class	
St1, St2 and St3 in Zone 22	
SRM 70/B1 .	52
Dust categories in accordance	
with EN 60335-2-69,	
Design approvals L, M, H,	
ATEX/B1, TLV .	54
Design approvals: dust categories	
in accordance with EN 60335-2-69 ..	
54	
Degree of filtration: design approvals,	
dust categories in accordance	
with EN 60335-2-69,	
L, M, H, ATEX/B1, TLV .	54
Dirt trap .	60
Dust bag for turbines .	68
Drills	
T 12+3 / T 15+3 .	84, 86
Drilling and screwdriving	
The system .	84, 91

E

Eccentric sanders	
WTS 150/7 .	8, 19
ETS 125 .	8, 19
ETS 150/3 .	8, 20
ETS 150/5 .	8, 20
Electric power tools .	18-20
ETS 125 .	19, 36
ETS 150/3 .	20
ETS 150/5 .	20
Extra handle RO/RAS/WTS .	29
Exhaust turbine	
TURBO 3091 .	48, 67
TURBO 4001 .	48, 67
TURBO 7501 .	48, 67
Extraction adapter .	63
Extension tube.	63
End cap .	63
Energy box	
EAA CT/SR (manual) .	76
EAA TURBO (manual) .	78

EAA TURBO (automatic). .	78
Elbow adapter FastFix. .	88
Extra long magnetic bit holder	
CENTROTEC .	90
Exhaust air extraction IAS 2 system .	10

F

Fine sanding, ultra-fine sanding. .	9
FastFix sanding pads .	26
Fleece - abrasive agent .	30-33
Fine polishing.	36
Finish cleaner.	36, 42
Fine sanding polish.	42
Filter bag .	61, 62
Floor nozzle .	64
Flat nozzle .	64
Floor cleaning set .	65
FastFix keyless chuck .	84, 88
FastFix eccentric attachment .	88
Foam insert SYS. .	97
Foam grid set SYS .	97

G

Gear-driven eccentric sander	
ROTEX RO 125	
ROTEX RO 150 .	8, 18, 39, 40
Guide coat black.	17, 26

H

HT Velcro (pad) .	21
Handle RO .	29
High gloss sealing.	36, 42
Holograms .	37
High gloss polish .	42
Hose storage .	60
Hose hook .	60
Hose holder CT/SR .	60
Hose sleeves .	63
Hand tube .	63
Heavy duty cleaning set .	65
Hose holder TC .	69

I

Intermediate sanding .	8
IAS 2 system .	10
IAS 2 connector .	14, 15, 58, 59, 68, 80
IAS 2 hose .	14, 58, 81
IAS 2 dual connector .	14, 58
Interface pad .	17, 26
Insert box SYS. .	97

J

Jetstream principle. .	21
Jet-Air cleaning system	
TURBO 3091 .	66
TURBO 4001 .	66
TURBO 7501 .	66

K

L	
LRS 400 .	11
LRS 93 G .	11
LRS 93 M .	11
Lochfix orbital sander.	27
Longlife filter bag .	61
Lashing strap TC .	69
Lid insert SYS .	97
Lid pad SYS .	97

M

Microfibre cloth .	42
Mobile dust extractor	
CTL MINI .	48, 50, 54/55
CTL MIDI .	48, 50, 54/55

Edited with the demo version of
Infix Pro PDF Editor
avalontools@yahoo.com
To remove this notice, visit:
www.iceni.com/unlock.htm

CTL 22-55 48, 51, 54/55
 CTM 22-55 48, 51, 54/55
 Main filter 61
 Main filter for turbines 68
 Magnetic bit holder CENTROTEC 90
 Maxi-Systainer 95
 Mini-Systainer 95

N

Nozzle cleaning set 65
 Nickel cadmium (NiCd) 84, 88
 Novadrive HSS twist drills 89
 Novadrive metal drill bit case 89

O

ORBITAL SANDER
 RS 100 8, 22
 RS 100 C 8, 22
 RS 200 8, 23
 RS 300 8, 23
 RTS 400 8, 24
 orange, medium 44

P

plug it
 Conversion kit 29
 Cable 29
 Connector 29
 Platin 2 - abrasive medium 30-31, 36
 Polishing 36
 Preliminary polishing 36
 Polishing - The Festool system 36-37
 Polishing out holograms 37, 41
 POLLUX 180 39
 Polishing agents 42
 Polishing pads 43
 Polishing sponge
 yellow, coarse 44
 Polishing felt
 hard 45
 Premium sheepskin 45
 Push handle 60
 Professional cleaning set 65
 Polishing, special applications:
 Product identification key 105
 Product performance features 105

Q

Quick charger 84, 89
 Quick-change bit holder CENTROTEC 90
 Quality and the environment 101
 Quality and the environment 101

R

ROTEX RO 150 8, 18, 37, 3
 ROTEX RO 125 8, 18, 37, 40
 RS 100 8, 22
 RS 100 C 8, 22
 RS 200 8, 23
 RS 300 8, 23
 RTS 400 8, 24
 Rotary sanders
 RAS 115 8, 25
 RAS 180 8, 25
 RAS 115 25
 RAS 180 25
 Round brush RAS 28
 Rotary polisher
 RAP 80 36, 38
 RAP 150 36, 38
 POLLUX 180 36, 39
 Rotating adapter 63
 Renovation cleaning set 65
 Rear wall TC 69
 Rolling base 98
 Replacement Parts 101

S

SYSTAINERs with inlays for
 Abrasives 2
 Sheepskin
 LEX 2 125/3 8, 12
 LEX 2 125/7 8, 12
 LEX 2 150/3 8, 12
 LEX 2 150/7 8, 12
 LEX 2 150/11 8, 13
 LEX 2 185/7 8, 13
 Sanding (overview) 8-9
 Sanding with compressed air 11
 Sanding pad brake 12, 13
 Sleeve 15, 59, 80
 Sanding pads, compressed air orbital sander
 16
 Sanding pads for compressed air
 Eccentric sanders
 hard 17
 soft 17
 ultra-soft 17
 Sanding, electric 18
 Sanding pads for gear-driven eccentric
 sanders and eccentric sanders
 hard 26
 soft 26
 ultra-soft 26
 StickFix sanding pads 26
 Sanding pads for abrasives
 for clamping 27
 Sanding pads ORBITAL SANDER 27
 StickFix sanding pad 27
 Sanding pads for rotary sanders
 hard 28
 soft 28
 Fibre discs 28
 Flexible sanding pads 28
 Spark trap for dust extractor 29, 60
 Suction hose, plug-it 29, 57, 81
 Suction hose 29, 81
 Saphir - abrasive agent 30-33
 Sanding stars 36, 42
 Spot sander 36, 42
 Spot repair 37
 Sanding polish 42
 soft 45
 Special purpose extractors
 SRM 45 52, 54/55
 SRM 70/B1 52, 54/55
 SRH 45 53, 54/55
 Suction hose, antistatic 57, 81
 Suction hose, non-antistatic 57, 81
 SR filters filter bags, discontinued models62
 Suction brush 64
 Special purpose nozzles/brushes 64
 Standard cleaning set 65
 SYSTAINER, SORTAINER,
 Systainer-Port - The system 94
 SYSTAINER
 SYS 1 95
 SYS 2 95
 SYS 3 95
 SYS 4 95
 SYS 5 95
 Maxi-Systainer 95
 Mini-Systainer 95
 SYSTAINER with inlays
 and inserts 96, 97
 SYSTAINER with inserts for
 Hand tools 97
 SORTAINER
 SYS 3-SORT/4 98
 SYS 3-SORT/6 98
 SYS 3-SORT/9 98
 SYS 3-SORT/12 98
 Systainer-Port SYS
 SYS-PORT 1000/2 98
 SYS-Port 500/2 98

Sales - Festool worldwide 106-107

T

Temperature resistant
 Velcro (HT pad) 21
 Titan 2 - abrasive agent 30-33
 TLV Threshold Limit Value:
 Design approvals, dust categories
 in accordance with EN 60335-2-69,
 L, M, H, ATEX/B1, TLV 54
 Two-ply filter bag 62
 Tubes (extractor accessories) 63
 Turbo combination suction brush 64
 TURBO 3091 67
 TURBO 4001 67
 TURBO 7501 67
 Toolcenter TC 3000 69
 TC 3000 69
 Tool holder TC 69
 T 12+3 86
 T 15+3 86
 Telescoping frame SYS 98
 Telescoping drawer SYS-PORT 98
 Tool cover SYS 98
 Tools for Profit customer club 101,

U

UV ceramic high gloss polish 42
 Upholstery nozzle 64
 Universal cleaning set 65
 Upgrade kit for turbines 68
 Universal inlays and
 deep-drawn inserts SYS 97

V

Vane motor 12, 13

W

WTS 150/7 8, 19
 Wet sanding 9
 white, fine 44
 white, fine (honeycombed) 44
 Wet filters 61
 Workshop cleaning set 65
 Wall mounting set EAA 80
 Worldwide Festool sales 106-107

Y


Y-connector, antistatic 63

Z

Edited with the demo version of
 Infrix Pro PDF Editor

To remove this notice, visit:
www.iceni.com/unlock.htm

Notes



StickFix

MMC electronics
Modern Multi Material Control™
power electronics provides adjustable table and constant speeds as well as temperature monitoring for work on all types of material.



General notes on the catalogue:

1. Please note that when using Festool products such as compressed air and power tools, together with their accessories and consumables, as well as handling hazardous substances or materials, the use of appropriate protective devices or the wearing of personal protective equipment is required. For information, please refer to the pertinent safety data sheets or, if you have any questions, contact the supervisory authorities responsible.
2. In the catalogue, if statements in regards to processing, such as amounts, time savings and surface areas processed are made, then these are average values that, depending upon the type of processed material/substance, can be significantly higher or lower. The manufacturer does not guarantee that these values will be reached in every individual case. Your Festool dealer is available to answer any questions in this regard.
3. All brand names, patents or other commercially protected rights remain the property of the respective owners, even if not explicitly stated. The use of information in this catalogue, especially of product names, trade names, product descriptions, etc., even if not expressly indicated, is not an authorisation that those names are to be regarded as free within the meaning of the trademark and brand protection laws and therefore may be used by any party.
4. The right to make modifications, especially to technical data or specifications, without prior notification, is reserved. Individual features may vary in accordance with country-specific conditions.
5. Products may differ from those pictured and the images may at times present components or parts that are not within the current range of available products. If you have any questions, please contact your Festool dealer.
6. We accept no liability for any errors or omissions.
7. Please consult the current price list for the manuf-

Jetstream principle
The 9-hole principle for reduced dust accumulation, less heat and less clogging. Providing up to a 30% longer service life!



FastFix
Facilitates the changing of routing, sawing, planing, sanding, drilling and screwdriving tools.



PoliStick
Fast fixing concept for attaching polishing felt, polishing sponges or sheepskins – for greater efficiency.



MPE sanding pad
Sanding pads and sanding discs from extremely durable materials for a long service life.



Dust extraction
Standard adapter (27/36/50 mm) for dust extraction to safeguard the operator and the environment.



IAS 2 system
Combines three functions in one hose: compressed air supply, exhaust air extraction and dust extraction.



Torque shutoff
Intelligent technology ensures tools run smoothly during sanding, which makes working less hazardous.



FlowDetect
Flow monitor check for a minimum air speed of 20 m/sec and issues a warning if the air speed falls below this value. To better protect your health.



Product identification key

Also included upon delivery

Packed in a Systemainer

Equipment variants

Performance class

Product type

RO | 150 | FEQ | Plus | Set

Set

**Albania**

KAST
Rruga „Durrest“, N-33, Laprake
P.O. Box 97
Tirana
Tel. 00355-4-35 78 00
Fax 00355-4-35 78 00
st_kast@yahoo.com

**Great Britain**

TTS Tooltechnic Systems (Shanghai) Ltd.
1159 Kangqiao East Rd, No.51-Buildg 1
Kangqiao Industrial Zone
201315 Shanghai (Pudong)
Tel. 0086-21-6818 2800
Fax 00355-4-35 78 00
info@festool.com.cn
www.festool.com.cn

**Jordan**

ADA A Trading & Decoration Co.
P.O. Box 640 Amman 11821
Tel. 00962 6 565 943
Fax 00962 6 565 061
info@adaatrading.com
www.adaatrading.com

**Canada**

Tooltechnic Systems LLC
.140 South Los Carneros Way
Goleta, CA 93117
USA
Tel. 001-805-968-0408
Fax 001-805-655-9788
sales@festoolusa.com
www.festoolusa.com

**India**

RAI Automotive Systems
302 & 303, 3rd floor, Competent house
F-14, Middle circle, Connaught Place
New Delhi 110 001
Tel. +91 11 4352-38610
Fax +91 11 22153131
raiauto@airtelmail.in
www.raiautomotive.com

**Denmark**

Festool GmbH
Wertstraße 20
DE-73240 Wendlingen a.N.
Tel. 0049-71 36 82
Fax 0034 938434320
bono@ts-festool.com
www.festool.net

**Argentina**

Festool GmbH
Wertstraße 20
DE-73240 Wendlingen a.N.
Tel. 0049-71 36 82
Fax 0034 938434320
bono@ts-festool.com
www.festool.com.au

**Australia**

TTS Tooltechnic Systems (AUST) PTY LTD
63-65 Quantum Close
Dandenong South VIC 3175
Postal address: PO Box 4401
Dandenong South VIC 3164
Tel. 0061-3 9799 9733
Fax 0061-3 9799 9766
festool@tooltechnic.com.au
www.festool.com.au

**Belgium**

Tooltechnic Systems (Belgium) N.V./S.A.
Merkverdeling/Distributeur FESTOOL
Rue Colonel Bourg 101
Bruxelles 1030 Brussels
Tel. 0032-2-702-32-38
Fax 0032-2-726-98-81
info-b@ts-festool.com
www.festool.be

**France**

TTS Tooltechnic Systems E.U.R.L.
Marque Festool
47 Grande Allée du 12 Février 1934
Noisiel
77448 Marne la Vallée Cedex 2
Tel. 0033-6-13060-0544
Fax 0033-6-160 06 62 26
mch@ts-festool.com
www.festool.com.br

**Brazil**

MAJO D.O.O.
Gorička pri Inhu 2
1230 Domžale (Slovenija)
Tel. 00386-17 248 216
Fax 00386-17 241 107
majodoo@sol.si
www.toolsystem.com.br

**Lebanon**

General Paint co. S.A.L.
P.O. Box 7623
St. Amelacha No. 2
El Taasi Zatone Iod
Tel. 00961-5-452 274
Fax 00961-9-925 993
genpaint@cdm-net.lb
www.festool.net

**Lithuania**

UAB TTS Tooltechnic Systems s.r.l.
Marchio: Festool
VIA Enrico Fermi 36-38
20090 Assago MI
Tel. 0039-02-4585296
Fax 0039-02-4585296
clama@ts-festool.bg
www.festool.lt

**Italy**

Edited with the demo version of
Infix Pro PDF Editor
To remove this notice, visit:
www.iceni.com/unlock.htm

**Georgia**

Alexport Company - Pontolac
19 Tamarashvili Str.
1592 Sofia
Tel. 00359-2-96 00 741
Fax 00359-2-96 00 743
ts@festool.bg

**Bulgaria**

Toolsystem Comercial Ltda.
Rua Simão Alves, 358
05417-020 São Paulo SP
Tel. 0055-11-3060-9300
Fax 0055-11-3060-0544
toolsystem@tsolysystem.com.br
www.festool.com.br



Malta

PIOVE HOLDINGS Ltd.
Triq id-Dielja 43
Qormi QRM 04
Tel. 00356-21 44 67 98
Fax 00356-21 44 44 76
piove@usa.net
www.festool.net



Portugal

TTS Tooltechnic Systems, S.L.U.
Paseo de la Zona Franca 69-73
08038 Barcelona (España)
Tel. 800 240 241
Fax 800 240 242
info-pt@tts-festool.com
www.festool-automotive.com



Spain

TTS Tooltechnic Systems, S.L.U.
Paseo de la Zona Franca 69-73
08038 Barcelona
Tel. 0034-93 264 30 30
Fax 0034-93 264 30 31
info-es@tts-festool.com
www.festool-automotive.com



Uruguay

Festool GmbH
Wertstraße 20
DE-73240 Wendingen a.N.
Tel. 0034 636 20 36 82
Fax 0034 938434320
bon@tts-festool.com
www.festool.net



Mexico

Etapel, S.A. de C.V.
California No. 167
Col. Parque San Andrés
Mexico, D.F. 04040
Tel. +525556895055
Fax +525556899911
mfbrandes@etapel.com.mx



Romania

S.C. AVALON TOOLS IMPEX SRL
Strada Ion Berindei nr.3
Bucuresti
Tel/Fax 0040-216 30 12 42
avalontools@yahoo.com
www.premiertc.ro



South Africa

TTS Tooltechnic Systems (PTY) LTD
22-26, Electron Avenue
P.O. Box 275
1600 Isando
Tel. 0027-11-570-28 80
Fax 0027-11-392-3651
info@festool.co.za
www.festool.co.za



USA

Tooltechnic Systems LLC
140 South Los Carneros Way
Goleta, CA 93117
Tel. 001-805-968-0408
Fax 001-805-685-9788
sales@festoolusa.com
www.festoolusa.com



New Zealand

Tooltechnic Systems (NZ) Ltd
27 Greenmount Drive
East Tamaki
Postal address: PO Box 258-078
Greenmount, Auckland
Tel. 0064 9 272-2220
Fax 0064 9 272-2230
sales@tooltechnic.co.nz
www.festool.co.nz



The Netherlands

Tooltechnic Systems BV
Coenecoop 715
2741 PW Waddinxveen
Tel. 0031-182-62 19 40
Fax 0031-182-62 19 49
info-nl@tts-festool.com
www.festool.nl



Russia

OOO TTS TOOLTECHNIC SYSTEMS
Krasnokazarmennaja ul., 13, str. 3
111250 Moscow
Tel. 007-495-72195 85
Fax 007-495-36122 09
info@tooltechnic.ru
www.festool.ru



Sweden

Tooltechnic Systems Sverige AB
Sadelgatan 9
21377 Malmö
Tel. 0046-40-38 20 80
Fax 0046-40-38 20 99
info-se@tts-festool.com
www.festool-automotive.com



Syria

I.T.C. Itcan Tool Center
Trade P.O. Box: 12521
Damascus
Tel. 00963-11-6222077
Fax 00963-11-62597122
itcan@alfarouk-ind.com
www.alfarouk-ind.com



Nigeria

Namtech Ltd.
Plot 4, Block A
Apapa/Oshodi Expressway
(Beside KIA Motors Plaza)
Lagos
Tel. 00234-1-7213166/7222153/4709511
Fax 00234-808-2046820-4
namtechgroup@yahoo.com



Switzerland

Tooltechnic Systems (Schweiz) AG
Moosmattstr. 24
8953 Dietikon
Tel. 0041-44 744 27 27
Fax 0041-44 744 27 28
info-ch@tts-festool.com
www.festool.ch



Taiwan

Bestor Trading Corp.
No.12, Chung-Yang Lane
Kuang-Pu Village Shetou
Hsiang Chang-Hua Hsien
Tel. 00-886-4-87266 97
Fax 00886-4-87252 09
bestor.steven@msa.hinet.net
www.festool.net



Vietnam

HafeleVina Co., Ltd
555 Ba Thang Hai Street
District 10
Ho Chi Minh City
Tel. 0084-8 957-3166
Fax 0084-8 957-3167
info@hafele.com.vn
www.hafele.com.vn



Norway

MOTEK A/S
Oestre Aker vei 61, Box 81 Oekern
N-0047 Oslo
Tel. 0047-23 05 25 00
Fax 0047-22 64 00 63
odd-arve.rygh@motek.no
www.motek.no



Serbia

M.A.S.S. Alati
Dragoslava Srejovica 83b
11060 Belgrad
Tel. 00381-112970064/2970063/2970062
velimir.jovanovic@massalati.co.yu
www.massalati.co.yu



Thailand

Keystone Siam Corp. Ltd.
100/48 Soi Nak Suwan
Nonsi Road
Yannawa
10120 Bangkok
Tel. 00662-681 3323
Fax 00662-681 3328
kscorpltd@hotmail.com
www.festool.net



Belarus

UAB TTS Tooltechnic Systems
Karaliaus Mindaugo pr. 21
44295 Kaunas (Lithuania)
Tel. 00370-37-323848
Fax 00370-37-323848
info-lt@tooltechnicsystems.com
www.festool.lt



Austria

Tooltechnic Systems Ges.m.b.H
Markenvertrieb Festool
Lützowgasse 14
1140 Wien
Tel. 0049-0-180 3 77 63 48
Fax 0049-0-7024 804 608
vertrieb@tooltechnicsystems.com
www.festool-automotive.com



Singapore

Hiap Huat Chemicals & Industrials Co.
149 Kaki Bukit Avenue 1
Shun Li Industrial Park
416009 Singapore
Tel. 0065-6745 4111
Fax 0065-6746 2977
joseph@hiaphuat.com.sg
www.festool.net



Turkey

Elmas Makine Ic ve Dis Tic. Ltd. Sti.
Berit 2 Villa 27 Ispartakule - Bahcesehir
34538 Istanbul
Tel. 0090-212-669 97 87
Fax 0090-212-669 36 16
festool@elmas-group.com
www.festool.net



Pakistan

Crisis management (PVT) LTD.
CM Engineering Technologies
C-1 Site Manghopir Road
75700 Karachi
Tel. 0092-2 12 56 50 55
Fax 0092-2 12 56 50 56
crisis@cyber.net.pk
www.cmcmt.com



Slovakia

TTS Slovakia s.r.o.
Jánosíkova 1
01001 Žilina
Tel. 00421-041-562-64 69
Fax 00421-041-562-47 91
festool@festool.sk
www.narex.sk/festool



Ukraine

Grushovenko Andriy
Polevaja str. 3a, office 4.
02230 Kiev
Tel. 0038-503 303 670
www.festool.net



Poland

Tooltechnic Systems (Polska) Sp.z.o.o.
ul. Mszczeńska 7
05-090 RASZYN, Janki k. Warszawy
Tel. 0048-22-7114 161 64
Fax 0048-22-7201 100 01
info-pl@tooltechnicsystems.com
www.festool.pl



Slovenia

MAJO D.O.O.
Goričica pri Izhanu 2
1230 Domžale
Tel. 00386-17 248 216
Fax 00386-17 241 107
majoo.doo@siol.net
www.majo.si



Hungary

Tooltechnic Systems K.f.t.
Besenye u.
1186 Budapest
Tel. 0036-1-297-13 50
Fax 0036-1-297-13 59
info@tooltechnicsystems.hu
www.festool.hu



FESTOOL

Scule pentru cele mai exigente pretentii

S.C. AVALON TOOLS IMPEX SRL
Bucuresti ROMANIA
Tel/Fax: 021-630.12.42
Mobil: 0723-99 11 76 / 0764-22 03 71
E-mail: avalontools@yahoo.com / office@premiertc.ro
www.premiertc.ro

The Festool 2009/2010 Automotive Catalogue



4 014549 104989



Edited with the demo version of
Infix Pro PDF Editor

To remove this notice, visit:
www.iceni.com/unlock.htm